SRI LANKA STANDARD 644 : 2014
UDC 631.83

SPECIFICATION FOR
POTASSIUM CHLORIDE
(FERTILIZER GRADE)
(First Revision)

SRI LANKA STANDARDS INSTITUTION

Sri Lanka Standard
SPECIFICATION FOR POTASSIUM CHLORIDE (FERTILIZER GRADE)
(First Revision)

SLS 644 : 2014

Gr. 4

SRI LANKA STANDARDS INSTITUTION
17, Victoria Place,
Elvitigala Mawatha,
Colombo 8
SRI LANKA

Sri Lanka Standards are subject to periodical revision in order to accommodate the progress made by industry. Suggestions for improvement will be recorded and brought to the notice of the Committees to which the revisions are entrusted.

This standard does not purport to include all the necessary provisions of a contract.

Sri Lanka Standard
SPECIFICATION FOR POTASSIUM CHLORIDE (FERTILIZER GRADE)
(First Revision)

FOREWORD

This standard was approved by the Sectoral Committee on Agriculture and was authorized for adoption and publication as a Sri Lanka Standard by the Council of the Sri Lanka Standards Institution on 2014-09-02.

This standard was first published in 1984. In this revision, two types have been identified with requirements for particle size. Requirement for magnesium content have been included and limits have been specified for potentially toxic elements.

This standard is subject to the restrictions imposed under the Regulation of Fertilizer Act No. 68 of 1988 of Sri Lanka, amendments and the regulations framed thereunder, where applicable.

Guidelines for the determination of compliance of a lot to the requirements of this standard based on statistical sampling and inspection are given in Appendix **A**.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or an analysis shall be rounded off in accordance with **SLS 102**. The number of significant places retained in the rounded off value shall be the same as that of the specified value in this standard.

In the preparation of this standard, the valuable assistance derived from the following publications are greatly appreciated AGP fertilizer specification of the Food and Agriculture Organization (FAO) of United Nations and the Association of Official Analytical Chemists (AOAC).

1 SCOPE

This standard prescribes the requirements and method of sampling and test for potassium chloride (muriate of potash) in granular form or crystalline powder used as a fertilizer.

2 REFERENCES

SLS 102 Rules for rounding off numerical values
SLS 124 Test sieves
SLS 544 Code of practice for handling and storage of bagged fertilizers
SLS 559 Method for sampling fertilizers

SLS 645 Methods of test for fertilizers
Part 2 Determination of moisture content
Part 7 Determination of sodium content
Official Methods of Analysis of the Association of Official Analytical Chemists (AOAC), 18th Edition, 2nd Revision 2007

3 TYPES

Potassium Chloride (fertilizer grade) covered in this standard shall be of the following types:

Type 1: Crystalline powder
Type 2: Granular

4 REQUIREMENTS

4.1 General requirements

4.1.1 *Type 1 Potassium chloride (Crystalline powder)*

The material shall be crystalline and white, light grey or pinkish in colour. It shall be free from visible contamination with clay or grit.

4.1.2 *Type 2 Potassium chloride (Granular)*

The material shall be granular and white, light grey or pinkish in colour. It shall be free from visible contamination with clay or grit.

4.1.3 Other requirements

4.2.1 *Particle size*

4.2.1.1 *Type 1: Potassium chloride (Crystalline powder)*

Not less than 65 per cent of the material shall passes through a sieve of aperture size of 1.7 mm and not more than 5 percent of the material shall passes through a sieve of aperture size of 0.25 mm when tested according to the method given in Appendix B. The test sieves shall conform to **SLS 124.**

4.2.1.2 *Type 2: Potassium chloride (Granular)*

Not less than 90 per cent of the material shall passes through a sieve of aperture size of 3.35 mm and not more than 5 percent of the material shall passes through a sieve of aperture size of 1 mm. The test sieves shall conform to **SLS 124.**

4.1.4 *Moisture and chemical requirements*

The material shall comply with the requirements given in Table **1** when tested according to the methods given in Column **4** of the table.

TABLE 1 – Moisture and chemical requirements for potassium chloride (for both types)

Sl. No. (1)	Characteristic (2)	Requirement (3)	Method of test (4)
i)	Moisture, per cent by mass, max.	1 .0	SLS 645 Part 2
ii)	Water soluble potassium content, as K_2O, percent by mass, min.	60	AOAC 983.02
iii)	Sodium, as NaCl, per cent by mass, max.	3 .5	SLS 645 Part 7
iv)	Magnesium, as $MgCl_2$, per cent by mass, max.	1 .0	AOAC 965.09

4.2.3 *Potentially toxic elements*

The material shall also comply with the requirements given in Table **2.**

TABLE 2 – Limits for potentially toxic elements for both types

Sl. No. (1)	Element (2)	Limit (3)	Method of test (4)
i)	Arsenic, as As, mg/kg, max.	0.3	AOAC Official Method 2006.3 ***(See the note)***
ii)	Cadmium, as Cd, mg/kg, max.	0.2	
iii)	Lead, as Pb, mg/kg, max.	0.2	
iv)	Chromium, as Cr, mg/kg, max.	10.0	
v)	Mercury, as Hg, mg/kg, max.	0.2	Atomic Absorption Spectrophotometry after microwave digestion

Note: *Atomic Absorption Spectrophotometry after microwave digestion can be used as an alternative method; AOAC 999.10 for Pb and Cd*

5 PACKAGING AND MARKING

5.1 Packaging

5.1.1 The material shall be suitably packed in sound, strong and moisture-proof multiwall paper bags, jute bags or woven polypropylene bags with polyethylene inner lining having a minimum thickness of 50 µm.

5.1.2 Each bag shall contain the mass of the product marked on the bag.

5.2 Marking

The packages shall be legibly and indelibly marked with the following information:

a) Name of the product as "*MURIATE OF POTASH (MOP) / POTASSIUM CHLORIDE (FERTILIZER GRADE)"*, in capital letters;
b) Registered trade mark if any;
c) Name and address of the manufacturer or importer or distributor and the country of origin;
d) Net mass, in kilograms;
e) The water soluble potassium content as K_2O, percent by mass;
f) Batch number or code number;
g) Date, month and the year of manufacture; and
h) The words "NO HOOK USED" in capital letters.

6. HANDLING AND STORAGE

The handling and storage of the material shall be as prescribed in **SLS 544**.

7. METHODS OF TEST

7.1 Tests shall be carried out as prescribed in AOAC Official Method **2006.3, AOAC 999.10, AOAC 965.09** and **AOAC 983.02**, Part **2** and **7** of **SLS 645** and Appendix **B** of this specification**.**

7.2 Unless otherwise stated, use only reagents of analytical grade and only distilled water or water of equivalent purity.

APPENDIX A
COMPLIANCE OF A LOT

The sampling scheme given in this appendix should be applied where compliance of a lot to the requirements of this standard is to be assessed based on statistical sampling and inspection.

Where compliance with this standard is to be assessed based on manufacture's control systems coupled with type testing and check tests or any other procedure, an appropriate scheme of sampling and inspection should be adopted.

A.1 SCALE OF SAMPLING

A.1.1. The sampling shall be carried out as prescribed in **SLS 559**.

A. 2 NUMBER OF TESTS

A.2.1 Each package selected as prescribed in **SLS 559** shall be inspected for packaging and marking requirements given in **5.**

A.2.2 Tests for the requirements given in **4** shall be carried out on the composite sample prepared as in **SLS 559.**

A.3 CRITERIA FOR CONFORMITY

A lot shall be declared as conforming to the requirements of this standard if the following conditions are satisfied:

A.3.1 Each package inspected as in **A.2.1** satisfy the relevant requirements.

A.3.2 The test results on the composite sample when tested as in **A.2.2** satisfy the relevant requirements.

APPENDIX B
DETERMINATION OF PARTICLE SIZE

B.1 PROCEDURE

B.1.1 Type 1 Crystalline Powder

B.1.1.1 Weigh, to the nearest 0.1 g, 50 g of the material and transfer to a sieve of 1.7 mm aperture size (conforming to **SLS 124**) with the lower receiver attached.

Shake the sieve for 5 minutes, frequently tapping the sides. Disintegrate soft lumps which can be crumbled by the application of the fibres of a soft brush, taking care that the hard part of the brush does not make contact with the sieve, and that the brush is not used to brush particles through the sieve. Brush out the powder in the lower receiver and weigh. Replace the receiver and repeat the shaking and tapping procedure for 2 minutes. Add the powder in the receiver to the first portion and weigh. Repeat the process until not more than 0.04 g passes through the sieve during 2 minutes.

B.1.1.2 Weigh, to the nearest 0.1 g, about 50 g of the material and transfer to a sieve of 0.25 mm aperture size (conforming to **SLS 124**) with the lower receiver attached and proceed as in **B.1.1.1.**

B.1.2 Type 2 Granular

B.1.2.1 Carry out the procedure given in **B.1.1.1** using a sieve size of 3.35 mm aperture size (conforming to **SLS 124**) with the lower receiver attached.

B.1.2.2 Carry out the procedure given in **B.1.1.2** using a sieve size of 1 mm aperture size (conforming to **SLS 124**) with the lower receiver attached.

B.2 CALCULATION

Calculate the mass of the material passed through the sieve as a percentage by mass of the material taken for the test.

SLS CERTIFICATION MARK

The Sri Lanka Standards Institution is the owner of the registered certification mark shown below. Beneath the mark, the number of the Sri Lanka Standard relevant to the product is indicated. This mark may be used only by those who have obtained permits under the SLS certification marks scheme. The presence of this mark on or in relation to a product conveys the assurance that they have been produced to comply with the requirements of the relevant Sri Lanka Standard under a well designed system of quality control inspection and testing operated by the manufacturer and supervised by the SLSI *which includes surveillance inspection of the factory, testing of both factory and market samples.*

Further particulars of the terms and conditions of the permit may be obtained from the Sri *Lanka Standards Institution, 17, Victoria Place, Elvitigala Mawatha, Colombo 08.*



Printed at SLSI (Printing Unit)

SRI LANKA STANDARDS INSTITUTION

The Sri Lanka Standards Institution (SLSI) is the National Standards Organization of Sri Lanka established under the Sri Lanka Standards Institution Act No. 6 of 1984 which repealed and replaced the Bureau of Ceylon Standards Act No. 38 of 1964. The Institution functions under the Ministry of Technology & Research.

The principal objects of the Institution as set out in the Act are to prepare standards and promote their adoption, to provide facilities for examination and testing of products, to operate a Certification Marks Scheme, to certify the quality of products meant for local consumption or exports and to promote standardization and quality control by educational, consultancy and research activity.

The Institution is financed by Government grants, and by the income from the sale of its publications and other services offered for Industry and Business Sector. Financial and Administrative control is vested in a Council appointed in accordance with the provisions of the Act.

The development and formulation of National Standards is carried out by Technical Experts and representatives of other interest groups, assisted by the permanent officers of the Institution. These Technical Committees are appointed under the purview of the Sectoral Committees which in return are appointed by the Council. The Sectoral Committees give the final Technical approval for the Draft National Standards prior to the approval by the Council of the SLSI.

All members of the Technical and Sectoral Committees render their services in an honorary capacity. In this process the Institution endeavours to ensure adequate representation of all view points.

In the International field the Institution represents Sri Lanka in the International Organization for Standardization (ISO), and participates in such fields of Standardization as are of special interest to Sri Lanka.

Printed at the Sri Lanka Standards Institution, 17, Victoria Place, Elvitigala Mawatha, Colombo 08