

**SRI LANKA STANDARD 1249 PART 2 : 2015**  
**ISO 13935 - 2 : 2014**  
**UDC 646.4**

**SEAM TEXTILE PROPERTIES AND MADE  
UP TEXTILE ARTICLES**  
**PART 2 : DETERMINATION OF MAXIMUM FORCE TO SEAM RAPTURE  
USING THE GRAB METHOD**  
**(First Revision)**

**SRI LANKA STANDARDS INSTITUTION**

**Sri Lanka Standard**  
**SEAM TEXTILE PROPERTIES AND MADE UP TEXTILE ARTICLES**  
**PART 2 : DETERMINATION OF MAXIMUM FORCE TO SEAM RAPTURE**  
**USING THE GRAB METHOD**  
**(First Revision)**

**SLS 1249 PART 2 : 2015**  
**ISO 13935 - 2 : 2014**

**Gr. E**

*Copyright Reserved*  
**SRI LANKA STANDARDS INSTITUTION**  
**17 Victoria Place**  
**Elvitigala Mawatha**  
**Colombo 8**  
**SRI LANKA.**

**Sri Lanka Standard**  
**SEAM TEXTILE PROPERTIES AND MADE UP TEXTILE ARTICLES**  
**PART 2 : DETERMINATION OF MAXIMUM FORCE TO SEAM RAPTURE**  
**USING THE GRAB METHOD**  
**(First Revision)**

**NATIONAL FOREWORD**

This standard was approved by the Sectoral Committee on Textiles, Clothing and Leather and was authorized for adoption and publication as a Sri Lanka Standard by the Council of the Sri Lanka Standards Institution on 2015-05-28.

This Sri Lanka Standard was first published in 2003 which was an adoption of ISO 13935-2 Textiles - Seam tensile properties of fabrics and made-up textile articles -- Part 2: Determination of maximum force to seam rupture using the grab method which has been revised in 2014. This first revision is an adoption of ISO 13935-1:2014 published by the International Organization for Standardization (ISO).

**TERMINOLOGY AND CONVENTIONS**

The text of the International Standard has been accepted as suitable for publication without deviation, as a Sri Lanka Standard. However certain terminology and conventions are not identical with those used in Sri Lanka Standards. Attention is therefore drawn to the following :

- a) Wherever the words “International Standard” appear referring to this standard they should be interpreted as “ Sri Lanka Standard ”.
- b) The comma has been used throughout as a decimal marker. In Sri Lanka Standards it is the current practice to use a full point on the baseline as the decimal marker.
- c) Whenever page numbers are quoted, they are ISO page numbers.

---

---

**Textiles — Seam tensile properties of  
fabrics and made-up textile articles —**

Part 2:

**Determination of maximum force to  
seam rupture using the grab method**

*Textiles — Propriétés de résistance à la traction des coutures d'étoffes  
et d'articles textiles confectionnés —*

*Partie 2: Détermination de la force maximale avant rupture des  
coutures par la méthode d'arrachement (Grab test)*



# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Principle</b> .....	<b>2</b>
<b>5 Sampling</b> .....	<b>2</b>
<b>6 Apparatus</b> .....	<b>2</b>
<b>7 Atmosphere for conditioning and testing</b> .....	<b>3</b>
<b>8 Preparation of seams and of test specimens</b> .....	<b>3</b>
8.1 Preparation of seams, if required, before testing.....	3
8.2 Dimensions.....	3
8.3 Preparation of test specimens.....	4
<b>9 Procedure</b> .....	<b>5</b>
9.1 Gauge length.....	5
9.2 Rate of extension.....	5
9.3 Mounting of test specimens.....	5
9.4 Operation.....	6
<b>10 Calculation and expression of results</b> .....	<b>6</b>
<b>11 Test report</b> .....	<b>6</b>
<b>Annex A (informative) Arrangements of jaws for the grab test</b> .....	<b>8</b>
<b>Bibliography</b> .....	<b>9</b>