SRI LANKA STANDARD 734 : PART 4 : 2017 UDC 621.316

SPECIFICATION FOR 13 A PLUGS, SOCKET-OUTLETS, ADAPTORS AND CONNECTION UNITS PART 4: SPECIFICATION FOR 13A FUSED CONNECTION UNITS SWITCHED AND UNSWITCHED

SRI LANKA STANDARDS INSTITUTION

Sri Lanka Standard SPECIFICATION FOR 13 A PLUGS, SOCKET-OUTLETS, ADAPTORS AND CONNECTION UNITS PART 4: SPECIFICATION FOR 13A FUSED CONNECTION UNITS SWITCHED AND UNSWITCHED

SLS 734: Part 4: 2017

(AMD 521 Attached)

Gr.19

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
17, Victoria Place
Elvitigala Mawatha
Colombo – 08
Sri Lanka

CONTENTS

PAGE

CLAUSE

0 Foreword	3
1 Scope	4
2 References	4
3 Terms and definitions	6
4 Conditions of use	8
5 General conditions for type testing	9
6 Classifications	10
7 Marking and labelling	11
8 Clearances, creepage distances and solid insulation	12
9 Accessibility of live parts	17
10 Provision for earthing	17
11 Terminals	18
12 Construction of connection units	23
13 Resistance to ageing, resistance to humidity and protection provided by enclosures	27
14 Insulation resistance and electric strength	31
15 Temperature rise	33
16 Breaking capacity of connection units	35
17 Normal operation of connection units	36
18 Connection of flexible cables and cable anchorage	
19 Mechanical strength	
20 Screws, current-carrying parts and connections	40
21 Resistance to heat	
22 Resistance to abnormal heat and fire	
23 Resistance to excessive residual stresses and to rusting	43
Tables	
TABLE 1 Schedule of tests.	
TABLE 2 Minimum clearances for basic insulation	
TABLE 3 Minimum creepage distances (mm) for basic insulation	
TABLE 4 Withstand voltages for insulation types	
TABLE 5 Torque values for screws and nuts	
TABLE 6 Actuator test force	
TABLE 7 Tightening torque values for cable gland	
TABLE 8 Test voltage across the open contacts for verifying the suitability for isolation, refer	
to the rated voltage and to the altitude where the test is carried out	
TABLE 9 Permitted temperature rises	
TABLE 10 Cable grip tests related to size of flexible cable	
TABLE D.1 Rated impulse withstand voltage for connection units energized directly from the	
voltage mains	
TABLE F.1 Test voltages for verifying clearances at sea level	59
Figures	
FIGURE 1 Solid link for test on fuse clips	
FIGURE 2 Pendulum impact test : General view of apparatus	
FIGURE 3 Pendulum impact test: Constructional details of striking elements	
FIGURE 4 Pendulum impact test: Constructional details of mounting support for test samples	
FIGURE 5 Calibrated link	
FIGURE 6 Calibration jig for calibrated link	49

Annexes

ANNEX A	The Construction and calibration of a calibrated Link	51
ANNEX B	Measurement of clearances and creepage distances	52
	Determination of the comparative tracking index (CTI) and proof tracking index (PTI)	
ANNEX D	Relation between rated impulse withstand voltage, rated voltage and overvoltage	
	category	57
ANNEX E	Pollution degree	
	Impulse voltage test	

Sri Lanka Standard SPECIFICATION FOR 13 A PLUGS, SOCKET-OUTLETS, ADAPTORS AND CONNECTION UNITS PART 4 SPECIFICATION FOR 13A FUSED CONNECTION UNITS SWITCHED AND UNSWITCHED

FOREWORD

This Standard was approved by the Sectoral committee on Electrical appliances and accessories and was authorized for adoption and publication as a Sri Lankan standard by the council of the Sri Lanka standards institution on 2017-06-14.

This standard is presented in five parts as given below and Part 1 and Part 2 are second revision of SLS 734: 1996 and other parts are newly included in this standard:

- Part 1: Specification for rewirable and non-rewirable 13A fused plugs
- Part 2: Specification for 13A switched and unswitched socket outlets
- Part 3: Specification for adaptors
- Part 4: Specification for 13A fused connection units, switched and unswitched
- Part 5: Specification fused conversion plugs

This is Part 4 of the SLS 734 and it specifies requirements for 13 A fused fixed connection units for household, commercial and light industrial purposes, with particular reference to safety in normal use.

All values given in this specification are in SI unit.

For the purpose of deciding whether a particular requirement of this standard is complied with the final value observed or calculated, expressing the results of a test or an analysis shall be rounded off in accordance with **SLS 102**. The number of figures to be retained in the rounded off values shall be the same as that of the specified value in this standard.

In the preparation of this standard, the assistance derived from the **BS 1363** for 13 A Plugs, Socket outlets, Adaptors and Connection units, Part **4: 2016** Specification for 13A Fused connection units switched and unswitched, is gratefully acknowledged.