

SRI LANKA STANDARD 1243 PART 2: 2021
(ISO 12945-2:2020)
UDC 677

**METHOD FOR DETERMINATION OF
FABRIC PROPENSITY TO SURFACE
PILLING, FUZZING OR MATTING –
PART 2- MODIFIED MARTINDALE
METHOD
(*First Revision*)**

SRI LANKA STANDARDS INSTITUTION

Sri Lanka Standard
METHOD FOR DETERMINATION OF FABRIC PROPENSITY TO SURFACE
PILLING, FUZZING OR MATTING –
PART 2- MODIFIED MARTINDALE METHOD
(First Revision)

SLS 1243 PART 2: 2021
(ISO 12945-2: 2020)

Gr. G

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
17, Victoria Place
Elvitigala Mawatha
Colombo - 08
Sri Lanka.

Sri Lanka Standard
METHOD FOR DETERMINATION OF FABRIC PROPENSITY TO SURFACE
PILLING, FUZZING OR MATTING –
PART 2- MODIFIED MARTINDALE METHOD

NATIONAL FOREWORD

This Sri Lanka Standard was approved by the Sectoral Committee on Textiles and Garment, and was authorized for adoption and publication as a Sri Lanka Standard by the Council of the Sri Lanka Standards Institution on 2021-12-22.

This is the first revision of **SLS 1243 – 2: 2002**, Method for determination of fabric propensity to surface fuzzing and to pilling - Part 2- modified Martindale method, which is the direct adoption of **ISO 12945 – 2: 2000**.

In 2020, **ISO 12945 - 2** has been revised for the first time with some important technical changes. The main change compared to the previous edition is, the assessment of pilling, fuzzing and matting is carried out according to the newly introduced part 4 of the same series. Therefore, the corresponding national Standard is found as necessary to be revised accordingly.

TERMINOLOGY AND CONVENTIONS

The text of the International Standard has been accepted as suitable for publication without deviation, as a Sri Lanka Standard. However certain terminology and conventions are not identical with those used in Sri Lanka Standards. Attention is therefore drawn to the following:

- a) Wherever the words “International Standard” appear referring to this standard they should be interpreted as “Sri Lanka Standard”.
- b) The comma has been used throughout as a decimal marker. In Sri Lanka Standards it is the current practice to use a full point on the baseline as the decimal marker.
- c) Whenever page numbers are quoted, they are ISO page numbers.

Second edition
2020-10

**Textiles — Determination of fabric
propensity to surface pilling, fuzzing
or matting —**

**Part 2:
Modified Martindale method**

*Textiles — Détermination de la propension au boulochage, à
l'ébouriffage ou au moutonnement des étoffes en surface —*

Partie 2: Méthode du Martindale modifiée



Reference number
ISO 12945-2:2020(E)

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Apparatus	2
6 Auxiliary materials	7
7 Preparation of test specimens	8
7.1 Pretreatment of the laboratory sample	8
7.2 Sampling of test specimens	8
7.3 Number of test specimens	8
7.4 Marking the test specimens	9
8 Conditioning and testing atmosphere	9
9 Procedure	9
9.1 General	9
9.2 Mounting the test specimens	9
9.2.1 Mounting the test specimen in the test specimen holder	9
9.2.2 Mounting the test specimen on the pilling table	9
9.3 Pilling test	10
10 Assessment of pilling, fuzzing and matting	10
11 Results	10
12 Test report	11
Annex A (normative) Categories of pilling test	12
Bibliography	13