

SRI LANKA STANDARD 1025 : Part 5 : 2009
IEC 60851-5 : 2008

**METHODS OF TEST
FOR WINDING WIRES
PART 5 : ELECTRICAL PROPERTIES**
(First Revision)

SRI LANKA STANDARDS INSTITUTION

Sri Lanka Standard
METHODS OF TEST FOR WINDING WIRES
PART 5: ELECTRICAL PROPERTIES
(First Revision)

SLS 1025 Part 5 : 2009
IEC 60851-5 : 2008

Gr. N

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
No. 17, Victoria Place
Elvitgiala Mawatha
Colombo 08
SRI LANKA.



INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Winding wires – Test methods –
Part 5: Electrical properties**

**Fils de bobinage – Méthodes d'essai –
Partie 5: Propriétés électriques**



CONTENTS

FOREWORD	4
INTRODUCTION	6
1 Scope	7
2 Normative references	7
3 Test 5: Electrical resistance	7
4 Test 13: Breakdown voltage	8
4.1 Principle	8
4.2 Equipment	8
4.3 Enamelled round wire with a nominal conductor diameter up to and including 0,100 mm	9
4.4 Enamelled round wire with a nominal conductor diameter over 0,100 mm up to and including 2,500 mm	10
4.4.1 Test at room temperature	10
4.4.2 Test at elevated temperature	11
4.5 Round wire with a nominal conductor diameter over 2,500 mm	12
4.5.1 Test at room temperature	12
4.5.2 Test at elevated temperature	14
4.6 Fibre wound round wire	14
4.6.1 Test at room temperature	14
4.6.2 Test at elevated temperature	16
4.7 Rectangular wire	16
4.7.1 Test at room temperature	16
4.7.2 Test at elevated temperature	16
5 Test 14: Continuity of insulation (applicable to enamelled round and tape wrapped round wire)	17
5.1 General	17
5.2 Low-voltage continuity (nominal conductor diameter up to and including 0,050 mm)	17
5.3 High-voltage continuity (nominal conductor diameter over 0,050 mm up to and including 1,600 mm)	17
5.3.1 Principle	17
5.3.2 Equipment	18
5.3.3 Procedure	21
5.3.4 Result	22
6 Test 19: Dielectric dissipation factor (applicable to enamelled wire and bunched wire)	22
6.1 Principle	22
6.2 Equipment	22
6.3 Specimen	23
6.3.1 Specimen for a metal bath electrode	23
6.3.2 Specimen for a conductive suspension electrode	23
6.4 Procedure	24
6.5 Result	24
7 Test 23: Pin hole test	24
Annex A (informative) Dissipation factor methods	25
Figure 1 – Arrangement of cylinder and specimen for the breakdown voltage test	10

Figure 2 – Device for twisting the specimen for breakdown voltage test	11
Figure 3 – U-bend specimen for the breakdown voltage test (specimen placed in shot bath)	13
Figure 4 – Coil-wound specimen for the breakdown voltage test	15
Figure 5 – Apparatus for testing the low-voltage continuity of covering	17
Figure 6 – High-voltage d.c. continuity – Pulleys for wire size 0,050 mm to 0,250 mm	19
Figure 7 – Pulley dimensions and spacing for wire size 0,250 mm to 1,600 mm	19
Figure 8a – Graphite fibre single brush electrode assembly	20
Figure 8b – Graphite fibre dual brush electrode assembly	21
Figure 8 – Graphite fibre single or dual brush electrode assembly	21
Figure 9 – Suitable electrode arrangement for testing the dielectric dissipation factor	23
Figure A.1 – Example of linear method for sole coating	27
Figure A.2 – Example of logarithmic method for sole coating	27
Table 1 – Rates of test voltage increase	8
Table 2 – Loads applied to the wire	9
Table 3 – Loads applied to the wire and number of twists	11
Table 4 – Fault currents	18
Table 5 – Test voltages	22