SRI LANKA STANDARD 1126 PART 1: 2020 (IEC 60095-1: 2018)

SPECIFICATION FOR LEAD-ACID STARTER BATTERIES PART 1: GENERAL REQUIREMENTS AND METHODS OF TEST

(Third Revision)

SRI LANKA STANDARDS INSTITUTION

Sri Lanka Standard SPECIFICATION FOR LEAD-ACID STARTER BATTERIES PART 1: GENERAL REQUIREMENTS AND METHODS OF TEST (Third Revision)

SLS 1126 Part 1: 2020 (IEC 60095-1: 2018)

Gr. M

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
No. 17, Victoria Place,
Elvitigala Mawatha,
Colombo – 08,
Sri Lanka.

SLS 1126 Part 1: 2020 IEC 60095-1: 2018

Edition 8.0

Sri Lanka Standard SPECIFICATION FOR LEAD-ACID STARTER BATTERIES Part 1: General requirements and methods of test

(Third Revision)

NATIONAL FOREWORD

This standard was approved by the Sectoral Committee on Electrical Appliances and Accessories and was authorized for adoption and publication as a Sri Lanka Standard by the Council of Sri Lanka Standards Institution on 2020-05-27.

This is the third revision of the **SLS 1126** Part**1:** 2020 and identical with **IEC 60095-1: 2018,** Edition 8.0 2018-11 Lead-Acid Starter Batteries Part 1: General requirements and methods of test published by the International Electrotechnical Commission (IEC).

Terminology and conventions

The text of the International Standard has been accepted as suitable for publication with additional information given in the **National Appendix**. However, certain terminology and conventions are not identical with those used in this Sri Lanka Standard; attention is therefore drawn to the following:

- a) Wherever the words "International Standard" appear referring to this standard they should be interpreted as "Sri Lanka Standard".
- b) Wherever the page numbers are quoted they are the page numbers of IEC standard.
- c) The comma has been used as a decimal marker. In Sri Lanka Standards it is the current practice to use a full point on the base line as a decimal marker

SLS 1126 Part 1: 2020 IEC 60095-1: 2018

Edition 8.0

CROSS REFERENCES

.

International Standard

Corresponding Sri Lanka Standard

IEC 60050-482: International Electrotechnical Vocabulary (IEV)

Chapter 482: Primary and secondary cells

and batteries

IEC 60095–2: Lead acid starter batteries Part 2: Dimensions of batteries and dimensions and marking of terminals

IEC 60095–4: Lead acid starter batteries Part 4: Dimensions of batteries for heavy trucks SLS 1126: Specification for Lead- acid starter batteries Part 2: Dimensions of batteries and dimensions and marking of terminals

SLS 1126: Lead acid starter batteries Part 3: Dimensions of batteries for heavy commercial vehicles

SLS 1126-1: 2020



IEC 60095-1

Edition 8.0 2018-11

INTERNATIONAL STANDARD



Lead-acid starter batteries -

Part 1: General requirements and methods of test



CONTENTS

F	DREWO	RD	4		
1	Scop	e	6		
2	Norm	native references	6		
3	Term	Terms and definitions			
4	Desid	Designation of starter batteries – Electrolyte density and open circuit voltage			
	4.1	Designation according to type			
	4.2	Dry-charged batteries			
	4.3	Electrolyte density and open circuit voltage			
5		lition on delivery			
6		eral requirements			
O	·				
	6.1	Identification, labelling			
	6.1.1				
	6.1.2				
	6.1.3 6.1.4	S .	٥		
	6.1.4	Capacity or reserve capacity (see 7.1.2) and nominal cranking current (see 7.1.1)	8		
	6.1.5				
	6.1.6				
	6.1.7	,			
	6.1.8				
	6.2	Marking of the polarity	9		
	6.3	Fastening of the battery	9		
7	Func	tional characteristics	10		
	7.1	Electrical characteristics	10		
	7.2	Mechanical characteristics	11		
8	Gene	eral test conditions	11		
	8.1	Sampling of batteries	11		
	8.2	Charging method – Definition of a fully charged battery			
	8.3	Test equipment			
	8.3.1	Measuring instruments	11		
	8.3.2	Water bath	12		
	8.3.3	Environmental chamber	12		
	8.4	Test sequence	12		
	8.4.1	Batteries filled and charged	12		
	8.4.2	Dry-charged or conserved-charge batteries	13		
9	Tests methods1				
	9.1	20 h capacity check $C_{\mathbf{e}}$	14		
	9.2	Reserve capacity check RCe	14		
	9.3	Cranking performance test	14		
	9.3.1	Cranking performance test – Standard temperature (-18 °C)	14		
	9.3.2	Cranking performance test – Very cold climates	15		
	9.3.3	High current discharge test at low temperature	15		
	9.4	Charge acceptance test	16		
	9.5	Charge retention test	16		
	9.6	Endurance test for batteries	16		

9.6.1	Corrosion test	16
9.6.2	Optional endurance cycle test for passenger car batteries – Maximum capacity 100 Ah	18
9.7	Water consumption test	19
9.8	Vibration resistance test	19
9.9	Electrolyte retention test	20
9.10	Cranking performance for dry-charged (or conserved-charge) batteries after activation	20
10 Requ	uirements	20
Annex A	(normative) Correlation between C_{n} and RC_{n}	22
Annex B	(informative) Water consumption test – Conversion of test temperatures and ions	
B.1	General	23
B.2	Conversion formula	
Annex C	(informative) Safety labelling	24
C.1	Definition of the six coloured symbols	24
C.2	Safety labelling – Label for North America area	
Bibliograp	phy	26
Figure C.	1 – Symbol dimensions	24
Figure C.	2 - Safety labelling - Label for North America area, former version (still valid)	25
Figure C.	3 – Safety labelling – Label for North America area, new version	25
Table 1 –	Charging method	11
Table 2 –	Accuracy of test equipment	12
Table 3 –	Test sequence	13
Table 4 –	Parameters cycle test	17
	Vibration resistance – Levels V1 to V3	
	Summary of requirements	
	Definition of safety symbols according to ISO 7010	