

**SRI LANKA STANDARD 1126 PART 2: 2022**  
**(IEC 60095-2:2021)**  
**UDC 621.35**

**SPECIFICATION FOR**  
**LEAD-ACID STARTER BATTERIES**  
**PART 2 : DIMENSIONS OF BATTERIES**  
**AND DIMENSIONS AND MARKING OF**  
**TERMINALS**  
*(Third Revision)*

**SRI LANKA STANDARDS INSTITUTION**

**Sri Lanka Standard**  
**SPECIFICATION FOR LEAD-ACID STARTER BATTERIES**  
**PART 2 : DIMENSIONS OF BATTERIES AND DIMENSIONS AND MARKING OF**  
**TERMINALS**  
*(Third Revision)*

**SLS 1126 Part 2: 2022**  
**(IEC 60095-2:2021)**

**Gr. S**

*Copyright Reserved*  
**SRI LANKA STANDARDS INSTITUTION**  
**No. 17, Victoria Place,**  
**Elvitigala Mawatha,**  
**Colombo 08.**  
**SRI LANKA**

**Sri Lanka Standard**  
**Specification for Lead-Acid Starter Batteries**  
**Part 2: Dimensions of batteries and dimensions and marking of terminals**  
*(Third Revision)*

**NATIONAL FOREWORD**

This standard was approved by the Sectoral Committee on Electrical Appliances and Accessories and was authorized for adoption and publication as a Sri Lanka Standard by the Council of Sri Lanka Standards Institution on 2022-06-02.

This is the third revision of the **SLS 1126 Part 2** and which is identical with **IEC 60095-2 Edition 5.0 2021-08** Lead-Acid Starter Batteries : Part 2 : Dimensions of batteries and dimensions and marking of terminals published by the International Electrotechnical Commission (IEC), except for the deviations given in the National Appendix.

For the purpose of deciding whether a particular requirement of this standard is complied with the final value, observed or calculated, expressing the results of a test or an analysis shall be rounded off in accordance with **SLS 102**. The number of significant places to be retained in the rounded off value shall be the same as that of the specified value in the standard.

**Terminology and conventions**

The text of the International Standard has been accepted as suitable for publication with additional information given in the National Appendix. However, certain terminology and conventions are not identical with those used in Sri Lanka Standards; attention is therefore drawn to the following:

- a) Wherever the words “International Standard” appear referring to this standard they should be interpreted as “Sri Lanka Standard”.
- b) Wherever the page numbers are quoted they are the page numbers of IEC standard.
- c) The comma has been used as a decimal marker. In Sri Lanka Standards it is the current practices to use a full point on the base line as a decimal marker.



# INTERNATIONAL STANDARD



---

**Lead-acid starter batteries –  
Part 2: Dimensions of batteries and dimensions and marking of terminals**







# INTERNATIONAL STANDARD



---

## Lead-acid starter batteries – Part 2: Dimensions of batteries and dimensions and marking of terminals

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 29.220.20; 43.040.10

ISBN 978-2-8323-0000-8

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references .....	7
3 Terms and definitions .....	7
4 General requirements .....	8
4.1 General.....	8
4.2 Marking.....	8
4.2.1 Safety labelling.....	8
4.2.2 Marking of the polarity of terminals .....	8
4.3 Recycling .....	9
4.3.1 Recycling of lead .....	9
4.3.2 Recycling of plastic material .....	9
4.4 Dimensions and design .....	9
4.5 Dimensions of tapered battery terminals .....	9
5 Recommended types used in Europe (EU).....	10
5.1 General.....	10
5.2 Main dimensions of batteries.....	10
5.3 Handles .....	14
5.3.1 General .....	14
5.3.2 Mounting of handles .....	14
5.4 Mounting of batteries .....	15
5.4.1 General .....	15
5.4.2 Dimensions and arrangement of ledges and notches .....	15
5.5 Terminals.....	16
5.5.1 Position of terminals .....	16
5.5.2 Dimensions of battery terminals.....	16
5.5.3 Marking of polarity .....	16
5.6 Special features of the battery lid.....	17
5.6.1 General .....	17
5.6.2 Semi bloc lid.....	17
5.6.3 Central degassing.....	17
5.6.4 Recessed holes .....	17
5.6.5 Removable cell plugs.....	18
5.6.6 Position of sensor openings.....	18
5.7 Handling of starter batteries by robot-equipment.....	19
5.8 Bulging and reinforcement of battery side walls .....	21
6 Other battery types used in Europe (EU) .....	22
6.1 General.....	22
6.2 Main dimensions of batteries.....	23
6.3 Handles .....	28
6.4 Mounting of batteries .....	28
6.4.1 General .....	28
6.4.2 Dimensions and arrangement of ledges and notches .....	28
6.5 Terminals.....	28
6.5.1 Position of terminals .....	28
6.5.2 Dimensions of battery terminals.....	28

6.5.3	Marking of polarity .....	28
6.6	Handling of starter batteries by robot-equipment .....	28
7	Recommended types used in North America (AM) .....	31
7.1	General.....	31
7.2	Terminals and terminal configuration .....	31
7.2.1	Tapered terminals.....	31
7.2.2	Side terminals.....	31
7.2.3	Terminal configuration .....	32
7.3	Standard fastening on the bottom .....	32
7.3.1	General .....	32
7.3.2	Design of ledges.....	32
7.3.3	Design of recesses .....	33
7.4	Main dimensions of the battery group sizes AM.....	37
8	Recommended types used in East Asia (AS) .....	42
8.1	General.....	42
8.2	Terminals and terminal configuration .....	42
8.2.1	Design of terminals.....	42
8.2.2	Dimensions and classification of terminals.....	42
8.2.3	Configuration of terminals.....	42
8.3	Main dimensions of the battery group sizes AS .....	42
Figure 1	– Marking of polarity .....	8
Figure 2	– Marking of polypropylene-polyethylene copolymer battery components .....	9
Figure 3	– Dimensions of positive (on the right) and negative (on the left) terminal .....	10
Figure 4	– Main dimensions of batteries of standard series LN and LBN – Top view .....	11
Figure 5	– Details of Figure 4.....	12
Figure 6	– Main dimensions of batteries of standard series LN – Front view .....	13
Figure 7	– Main dimensions of batteries of standard series LN – Side view.....	14
Figure 8	– Details of ledges of Figure 6 and Figure 7 .....	16
Figure 9	– Detail X – Notch on ledge.....	16
Figure 10	– Degassing outlet .....	17
Figure 11	– Recessed holes "M" for optional terminal protection .....	18
Figure 12	– Removable cell plugs and sensor positions .....	19
Figure 13	– Grips for handling by robot equipment.....	20
Figure 14	– Section P-P of Figure 13 and Figure 22.....	20
Figure 15	– Detail U of Figure 13 and Figure 22.....	21
Figure 16	– Maximum allowed bulging on short sides.....	21
Figure 17	– Reinforcement by thicker walls on short sides .....	22
Figure 18	– Reinforcement by additional ribs on short sides.....	22
Figure 19	– Main dimensions of batteries of series L, LB, E, EB .....	26
Figure 20	– Main dimensions of batteries of series LS, LBS, ES, EBS .....	27
Figure 21	– Details of Figure 19 and Figure 20 .....	27
Figure 22	– Grips for handling by robot equipment for LBN series.....	29
Figure 23	– Grips for handling by robot equipment for L and LS series .....	29
Figure 24	– Detail V of Figure 23 .....	30

Figure 25 – Grips for handling by robot equipment for LB and LBS series – Option 1 .....	30
Figure 26 – Grips for handling by robot equipment for LB and LBS series – Option 2 .....	30
Figure 27 – Detail Y of Figure 25 and Figure 26 .....	31
Figure 28 – Side terminal groove description .....	32
Figure 29 – Side terminal groove dimensions in mm and (in) .....	32
Figure 30 – Design for batteries with ledges on long sides for hold-down-devices in mm and (in) .....	33
Figure 31 – Design for batteries with recesses on long sides for hold-down-devices in mm and (in) .....	34
Figure 32 – Design for batteries with recesses on sides for hold-down-devices in mm and (in) .....	35
Figure 33 – Design for batteries with recesses on sides for hold-down-devices in mm and (in) .....	36
Figure 34 – Design for batteries with recesses on sides for hold-down-devices in mm and (in) .....	37
Figure 35 – Main dimensions of batteries of group sizes 24R, 26R, 34R, 35, 51R, 85 .....	39
Figure 36 – Main dimensions of batteries of group size 24, 25, 26, 27, 34, 51, 86 .....	39
Figure 37 – Main dimensions of batteries of group size 36R .....	40
Figure 38 – Main dimensions of batteries of group sizes 59, 65 .....	40
Figure 39 – Main dimensions of batteries of group size 75, 78,100 with positive terminal on the right .....	41
Figure 40 – Main dimensions of batteries of group size 75, 78,100 with positive terminal on the left .....	41
Figure 41 – Main dimensions of battery group sizes AS .....	43
Table 1 – Main dimensions of batteries of standard series LN .....	11
Table 2 – Main dimensions of batteries of other series LBN .....	23
Table 3 – Main dimensions of other series L, LS, LB and LBS .....	24
Table 4 – Main dimensions of other series E, ES, EB and EBS .....	25
Table 5 – Battery group sizes AM .....	38
Table 6 – Dimensions and classification of terminals .....	42
Table 7 – Dimensions of group sizes AS .....	43