SRI LANKA STANDARD

SLS ISO 3951-2: 2016 UDC 543.05

SAMPLING PROCEDURES FOR INSPECTION BY VARIABLES –

PART 2: GENERAL SPECIFICATION FOR SINGLE SAMPLING PLANS INDEXED BY ACCEPTANCE QUALITY LIMIT (AQL) FOR LOT-BY-LOT INSPECTION OF INDEPENDENT QUALITY CHARACTERISTICS

SRI LANKA STANDARDS INSTITUTION

Sri Lanka Standard SAMPLING PROCEDURES FOR INSPECTION BY VARIABLES – PART 2: GENERAL SPECIFICATION FOR SINGLE SAMPLING PLANS INDEXED BY ACCEPTANCE QUALITY LIMIT (AQL) FOR LOT-BY-LOT INSPECTION OF INDEPENDENT QUALITY CHARACTERISTICS

SLS ISO 3951-2: 2016 (ISO 3951-2: 2013)

Gr.X

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
No. 17, Victoria Place
Elvitigala Mawatha
Colombo 08
SRI LANKA

SLS ISO 3951-2: 2016 ISO 3951-2: 2013

Sri Lanka Standard SAMPLING PROCEDURES FOR INSPECTION BY VARIABLES – PART 2: GENERAL SPECIFICATION FOR SINGLE SAMPLING PLANS INDEXED BY ACCEPTANCE QUALITY LIMIT (AQL) FOR LOT-BY-LOT INSPECTION OF INDEPENDENT QUALITY CHARACTERISTICS

NATIONAL FOREWORD

This standard was approved by the Sectoral Committee on Building and Construction Materials and was authorized for adoption and publication as a Sri Lanka Standard by the Council of the Sri Lanka Standard Institution on 2016-07-22.

This Sri Lanka Standard is identical with **ISO 3951-2: 2013**, published by the International Organization for Standardization (**ISO**).

This Sri Lanka standard specifies an acceptance sampling system of single sampling plans for inspection by variables. It is indexed in terms of the acceptance quality limit (AQL).

TERMINOLOGY AND CONVENTIONS

The text of the International Standard has been accepted as suitable for publication as a Sri Lanka Standard. However, certain terminology and conventions are not identical with those used in Sri Lanka Standards.

Attention is therefore drawn to the following:

- a) Wherever the "International Standard" appear referring to this standard they should be interpreted as "Sri Lanka Standard".
- b) Wherever page numbers are quoted, they are "**ISO**" page numbers.
- c) The coma has been used throughout as a decimal marker. In Sri Lanka Standards it is the current practice to use a full point on the base line as the decimal marker.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test method or observation shall be rounded off in accordance with **SLS 102**. The number of significant places retained in the rounded off value shall be the same as that of the specified value in this standard.

INTERNATIONAL STANDARD

SLS ISO 3951-2:2016 **ISO 3951-2**

Second edition 2013-09-01

Sampling procedures for inspection by variables —

Part 2:

General specification for single sampling plans indexed by acceptance quality limit (AQL) for lot-by-lot inspection of independent quality characteristics

Règles d'échantillonnage pour les contrôles par mesures —

Partie 2: Spécification générale pour les plans d'échantillonnage simples indexés par une limite de qualité acceptable (LQA) pour le contrôle lot par lot de caractéristiques-qualité indépendantes



Coi	ntents	Page	
Fore	word	v	
Intro	oduction	vi	
1	Scope	1	
2	Normative references		
3			
4	Symbols		
	4.1 Univariate symbols		
	4.2 Multivariate symbols	8	
5	Acceptance quality limit (AQL)		
	5.1 Concept		
	5.3 Specifying AQLs		
	5.4 Preferred AQLs	9	
	5.5 Caution		
_	5.6 Limitation		
6	Switching rules for normal, tightened, and reduced inspection		
7	Relation to ISO 2859-1 and ISO 3951-1 7.1 Relation to ISO 2859-1		
	7.1 Relation to ISO 2859-1 7.2 Relation to ISO 3951-1		
8	Consumer protection		
0	8.1 Use of individual plans		
	8.2 Consumer's risk quality (CRQ) tables		
	8.3 Producer's risk tables		
	8.4 Operating characteristic (OC) curves		
9	Accommodating measurement variability		
10	Planning	13	
11	Choice between variables and attributes	13	
12	Choice between the s -method and σ -method	14	
13	Choice of inspection level and AQL	14	
14	Choice of sampling scheme	14	
	14.1 Standard plans		
	14.2 Special plans		
15	Preliminary operations	15	
16	Standard procedures for the univariate s-method		
	16.1 Obtaining a plan, sampling, and preliminary calculations k acceptability criterion for the s -method		
	 16.2 Form k acceptability criterion for the s-method 16.3 Form p* acceptability criterion for the s-method 		
17	Standard multivariate s-method procedures for independent quality characteristics		
	17.1 General methodology		
	17.2 Example	25	
18	Standard univariate σ -method procedures	27	
	18.1 Obtaining a plan, sampling, and preliminary calculations		
	18.2 Acceptability criterion for a single specification limit or for double specification limit with separate control		
	18.3 Acceptability criterion for double specification limits with combined or	20	
	complex control	29	

19	Stand 19.1 19.2	ard multivariate σ -method procedures for independent quality characteristics	31
20	Stand	ard multivariate combined s -method and σ -method procedures for independent	
	quali	ty characteristics	32
	20.1 20.2	General methodology Example	
21		edure during continuing inspection	
22	Norm 22.1	ality and outliers Normality	
	22.2	Outliers	
23	Recor	rds	35
	23.1	Control charts	
	23.2	Lots that are not accepted	
24	•	ation of switching rules	
25		ntinuation and resumption of inspection	
26		hing between the s-method and σ-method	
	26.1 26.2	Estimating the process standard deviation	
	26.3	Switching from the s -method to the σ -method	
	26.4	Switching from the σ -method to the s -method	
Anne	x A (no	rmative) Table for determining the sample size code letter	38
Anne	x B (no	rmative) Form k single sampling plans: s-method	39
Anne	x C (noi	mative) Form k single sampling plans: σ-method	42
Anne	x D (no	rmative) Form p* single sampling plans: s-method	45
Anne	x E (noi	mative) Form p* single sampling plans: σ-method	48
Anne	x F (noi	mative) Values of f_S for maximum sample standard deviation (MSSD)	51
Anne	x G (no	rmative) Values of f_σ for maximum process standard deviation (MPSD)	54
Anne		rmative) Estimating the process fraction nonconforming for sample size	
		nethod	
Anne	x I (nor	mative) Values of $c_{ m U}$ for upper control limit on the sample standard deviation	60
Anne		mative) Supplementary acceptability constants for qualifying towards ed inspection	61
Anne	x K (no	rmative) Procedures for obtaining s and σ	62
Anne	x L (noi	mative) Estimating the process fraction nonconforming	64
Anne	x M (inf	formative) Consumer's risk qualities	70
		ormative) Producer's risks	
Anne	x O (inf	ormative) Operating characteristics for the σ-method	78
		ormative) Accommodating measurement variability	
		V	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

The committee responsible for this document is ISO/TC 69, *Application of statistical methods*, Subcommittee SC 5, *Acceptance sampling*.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: http://www.iso.org/iso/home/standards_development/resources-fortechnical-work/foreword.htm

This second edition cancels and replaces the first edition (ISO 3951-2:2006), of which it constitutes a minor revision with the following changes:

- procedures have been introduced to accommodate measurement uncertainty;
- many of the sampling plans have been adjusted to improve the match between their operating characteristic curves and the operating characteristic curves of the corresponding plans for single sampling by attributes in ISO 2859-1.

ISO 3951 consists of the following parts, under the general title *Sampling procedures for inspection by variables*:

- Part 1: Specification for single sampling plans indexed by acceptance quality limit (AQL) for lot-by-lot inspection for a single quality characteristic and a single AQL
- Part 2: General specification for single sampling plans indexed by acceptance quality limit (AQL) for lot-by-lot inspection of independent quality characteristics
- Part 3: Double sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection
- Part 4: Procedures for assessment of declared quality levels
- Part 5: Sequential sampling plans indexed by acceptance quality limit (AQL) for inspection by variables (known standard deviation)