SRI LANKA STANDARD 1543 PART 1: 2016

IEC 62109 - 1 : 2010 UDC 621.311

SPECIFICATION FOR SAFETY OF POWER CONVERTERS FOR USE IN PHOTOVOLTAIC POWER SYSTEMS

PART 1: GENERAL REQUIREMENTS

SRI LANKA STANDARDS INSTITUTION

Sri Lanka Standard Specification for SAFETY OF POWER CONVERTERS FOR USE IN PHOTOVOLTAIC POWER SYSTEMS PART 1: GENERAL REQUIREMENTS

SLS 1543 Part 1 : 2016 IEC 62109 - 1 : 2010

Gr. Z

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
17, Victoria Place
Elvitigala Mawatha
Colombo 8
Sri Lanka

SLS 1543 Part 1 : 2016 IEC 62109 -1 : 2010

Edition 1.0

Sri Lanka Standard Specification for SAFETY OF POWER CONVERTERS FOR USE IN PHOTOVOLTAIC POWER SYSTEMS PART 1 : GENERAL REQUIREMENTS

NATIONAL FOREWORD

This standard was approved by the Sectoral Committee on Electronic Engineering and was authorized for adoption and publication as a Sri Lanka Standard by the Council of Sri Lanka Standards Institution on 2016-11-24.

SLS 1543 Sri Lanka Standard Specification for Safety of power converters for use in photovoltaic power systems is published in two parts as follows:

Part 1: General requirements

Part 2: Particular requirements for inverters

This part of standard is identical with IEC 62109, Safety of power converters for use in photovoltaic power systems, Part 1: 2010 Edition 1.0 General requirements, published by the International Electrotechnical Commission (IEC).

All values given in this standard is in SI units.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or an analysis shall be rounded off in accordance with SLS 102, in case if the method of rounding off is not specified in the text of this standard. The number of figures to be retained in the rounded off value, shall be the same as that of the specified value in this standard.

Terminology and conventions

The text of the International Standard has been accepted as suitable for publication, without any deviation as a Sri Lanka Standard. However, certain terminology and conventions are not identical with those used in Sri Lanka Standards; attention is therefore drawn to the following:

- a) Wherever the words "International Standard" appear referring to this standard they should be interpreted as "Sri Lanka Standard".
- b) Wherever the page numbers are quoted they are the page numbers of IEC standard.
- c) The comma has been used as a decimal marker. In Sri Lanka Standards it is the current practices to use a full point on the base line as a decimal marker.
- d) Attention is drawn to the possibility that some of the elements of the Sri Lanka Standard may be the subject of patent rights. SLSI shall not be held responsible for identifying any or all such patent rights.



IEC 62109-1

Edition 1.0 2010-04

INTERNATIONAL STANDARD



Safety of power converters for use in photovoltaic power systems – Part 1: General requirements



CONTENTS

FC	REW	ORD		8	
IN	TROD	UCTION	N	10	
1	Scope and object			11	
	1.1	Scope		11	
		1.1.1	Equipment included in scope	11	
		1.1.2	Equipment for which other requirements may apply		
	1.2	Object	t		
		1.2.1	Aspects included in scope	11	
		1.2.2	Aspects excluded from scope	12	
2	Norn	native re	eferences	12	
3	Tern	erms and definitions			
4	General testing requirements				
	4.1		al		
	4.2		al conditions for testing		
		4.2.1	Sequence of tests		
		4.2.2	Reference test conditions		
	4.3	Therm	al testing		
		4.3.1	General		
		4.3.2	Maximum temperatures		
	4.4		g in single fault condition		
		4.4.1	General		
		4.4.2	Test conditions and duration for testing under fault conditions	31	
		4.4.3	Pass/fail criteria for testing under fault conditions		
		4.4.4	Single fault conditions to be applied		
	4.5	Humidity preconditioning		36	
		4.5.1	General	36	
		4.5.2	Conditions	36	
	4.6	Backfeed voltage protection		36	
		4.6.1	Backfeed tests under normal conditions	37	
		4.6.2	Backfeed tests under single-fault conditions	37	
		4.6.3	Compliance with backfeed tests	37	
	4.7	Electri	ical ratings tests	37	
		4.7.1	Input ratings	37	
		4.7.2	Output ratings	37	
5	Marking and documentation				
	5.1	Marking		37	
		5.1.1	General	37	
		5.1.2	Durability of markings	38	
		5.1.3	Identification	38	
		5.1.4	Equipment ratings	38	
		5.1.5	Fuse identification	38	
		5.1.6	Terminals, connections and controls	39	
		5.1.7	Switches and circuit-breakers	39	
		5.1.8	Class II equipment	39	
		5.1.9	Terminal boxes for external connections		
	5.2	2 Warning markings			

		5.2.1	Visibility and legibility requirements for warning markings	40
		5.2.2	Content for warning markings	40
		5.2.3	Sonic hazard markings and instructions	41
		5.2.4	Equipment with multiple sources of supply	41
		5.2.5	Excessive touch current	41
	5.3	Docum	nentation	42
		5.3.1	General	42
		5.3.2	Information related to installation	42
		5.3.3	Information related to operation	43
		5.3.4	Information related to maintenance	44
6	Environmental requirements and conditions			44
	6.1	Enviro	nmental categories and minimum environmental conditions	45
		6.1.1	Outdoor	45
		6.1.2	Indoor, unconditioned	45
		6.1.3	Indoor, conditioned	45
	6.2	Pollutio	on degree	46
	6.3	Ingres	s protection	47
	6.4	UV exp	oosure	47
	6.5	Tempe	erature and humidity	47
7	Prote	ection a	gainst electric shock and energy hazards	47
	7.1	Genera	al	47
	7.2	Fault c	onditions	47
	7.3	Protec	tion against electric shock	48
		7.3.1	General	48
		7.3.2	Decisive voltage classification	48
		7.3.3	Protective separation	52
		7.3.4	Protection against direct contact	52
		7.3.5	Protection in case of direct contact	57
		7.3.6	Protection against indirect contact	60
		7.3.7	Insulation including clearance and creepage distances	68
		7.3.8	Residual Current Detection (RCD) or Monitoring (RCM) device compatibility	79
		7.3.9	Protection against shock hazard due to stored energy	80
	7.4	Protec	tion against energy hazards	80
		7.4.1	Determination of hazardous energy level	80
		7.4.2	Operator access areas	81
		7.4.3	Service access areas	81
	7.5	Electri	cal tests related to shock hazard	81
		7.5.1	Impulse voltage test (type test)	81
		7.5.2	Voltage test (dielectric strength test) (type test and routine test)	83
		7.5.3	Partial discharge test (type test or sample test)	87
		7.5.4	Touch current measurement (type test)	88
		7.5.5	Equipment with multiple sources of supply	89
8	Prote	Protection against mechanical hazards		
	8.1	Genera	al	89
	8.2	Moving	parts	90
		8.2.1	Protection of service persons	90
	8.3	Stability		90
	8.4	Provisions for lifting and carrying		91

	8.5 Wall mounting			91
	8.6 Expelled parts			92
9	Protection against fire hazards			92
	9.1	Resista	ance to fire	92
		9.1.1	Reducing the risk of ignition and spread of flame	92
		9.1.2	Conditions for a fire enclosure	93
		9.1.3	Materials requirements for protection against fire hazard	93
		9.1.4	Openings in fire enclosures	96
	9.2	Limited	I power sources	100
		9.2.1	General	100
		9.2.2	Limited power source tests	100
	9.3	Short-c	circuit and overcurrent protection	101
		9.3.1	General	101
		9.3.2	Number and location of overcurrent protective devices	101
		9.3.3	Short-circuit co-ordination (backup protection)	102
10	Prote	ction ag	gainst sonic pressure hazards	102
	10.1	Genera	al	102
	10.2	Sonic p	pressure and sound level	102
		10.2.1	Hazardous noise levels	102
11	Prote	ction ag	gainst liquid hazards	103
	11.1	Liquid (containment, pressure and leakage	103
			ressure and leakage	
		•	Maximum pressure	
			Leakage from parts	
			Overpressure safety device	
	11.3		grease	
12			zards	
	12.1	Genera	al	104
13			uirements	
	•	•	s and manual controls	
	13.1		Adjustable controls	
	13.2		ng of parts	
			ons for external connections	
	13.3		General	
			Connection to an a.c. mains supply	
			Wiring terminals for connection of external conductors	
			Supply wiring space	
			Wire bending space for wires 10 mm ² and greater	
			Disconnection from supply sources	
			Connectors, plugs and sockets	
			Direct plug-in equipment	
	13 /		I wiring and connections	
	13.4		General	
			Routing	
			Colour coding	
			Splices and connections	
			Interconnections between parts of the PCE	
	13 5		ags in enclosures	
	10.0	Openin	ıyə iii eiiolosules	1 1 4

		13.5.1	Top and side openings	.114
	13.6	Polyme	ric materials	.116
			General	.116
		13.6.2	Polymers serving as enclosures or barriers preventing access to	117
		1363	hazards Polymers serving as solid insulation	
			UV resistance	
	13 7		nical resistance to deflection, impact, or drop	
	10.7		General	
			250 N deflection test for metal enclosures	
			7 J impact test for polymeric enclosures	
			Drop test	
	13.8		ess requirements for metal enclosures	
			General	
		13.8.2	Cast metal	. 120
		13.8.3	Sheet metal	.120
14	Comp	onents		.122
	14.1	Genera	ıl	. 122
	14.2	Motor o	overtemperature protection	. 124
	14.3	Overte	mperature protection devices	.124
	14.4	Fuse h	olders	.124
	14.5	Mains	voltage selecting devices	.124
	14.6	Printed	circuit boards	.124
	14.7	Circuits	or components used as transient overvoltage limiting devices	. 125
	14.8	Batterie	9S	. 125
		14.8.1	Battery enclosure ventilation	. 125
		14.8.2	Battery mounting	. 126
			Electrolyte spillage	
			Battery connections	
			Battery maintenance instructions	
			Battery accessibility and maintainability	
			firmware performing safety functions	
Ann	ex A	(normat	ve) Measurement of clearances and creepage distances	. 128
Ann	ex B ((normat	ve) Programmable equipment	. 133
Ann	ex C	(normat	ive) Symbols to be used in equipment markings	. 134
Ann	ex D	(informa	tive) Test probes for determining access	. 136
Ann	ex E ((informa	tive) RCDs	. 138
Ann	ex F (· informa	tive) Altitude correction for clearances	. 140
			ative) Clearance and creepage distance determination for frequencies	
grea	ater th	an 30 k	Hz	.141
			tive) Measuring instrument for touch current measurements (see	. 144
	•		ive) Examples of protection, insulation, and overvoltage category	-
			PCÉ	. 146
Ann	ex J (normati	ve) Ultraviolet light conditioning test	. 150
_			onal summary of protective measures against electric shock	
Figu	ıre 2 -	- Typica	ıl waveform for a.c. working voltage	51

Figure 3 – Typical waveform for d.c. working voltage	51
Figure 4 – Typical waveform for pulsating working voltage	52
Figure 5 – Examples for protection against direct contact for DVC-C circuits	56
Figure 6 – Protection by DCV A with protective separation	57
Figure 7 – Protection by means of protective impedance	58
Figure 8 – Protection by limitation of discharge energy	59
Figure 9 – Protection by means of voltage limitation	60
Figure 10 – Examples of protective bonding and earthing	61
Figure 11 – Protective bonding impedance test for separate unit with power fed from the PCE with overcurrent protection for the power cable	63
Figure 12 – Protective bonding impedance test for separate unit with accessible parts and with power fed from the PCE without overcurrent protection	64
Figure 13 – Voltage test procedures	85
Figure 14 – Fire enclosure bottom openings below an unenclosed or partially enclosed component	97
Figure 15 – Fire enclosure baffle construction	98
Figure 16 – Examples of cross-sections of designs of openings preventing vertical access	115
Figure 17 – Examples of louver design	115
Figure 18 – Enclosure openings	116
Figure 19 – Methods of compliance verification	123
Figure A.1 – Narrow groove	128
Figure A.2 – Wide groove	129
Figure A.3 – V-shaped groove	129
Figure A.4 – Rib	
Figure A.5 – Uncemented joint with narrow groove	
Figure A.6 – Uncemented joint with wide groove	
Figure A.7 – Uncemented joint with narrow and wide grooves	
Figure A.8 – Narrow recess	
Figure A.9 – Wide recess	
Figure A.10 – Intervening, unconnected conductive part	
Figure A.11 – Distance for multilayer PWBs	
Figure D.1 – Test finger	
Figure D.2 – Test pin	
Figure D.3 – Straight unjointed test finger	
Figure E.1 – Flow chart leading to selection of the RCD/RCM type upstream of a PCE	
Figure G.1 – Clearance distance determination for frequencies greater than 30 kHz	
Figure G.2 – Creepage distance determination for frequencies greater than 30 kHz	
Figure H.1 – Measuring instrument	
Figure H.2 – Alternative measuring instrument	
Figure I.1 – Transformer (basic) isolated PV inverter with SPD to reduce impulse.	147
Figure I.2 – Transformer (basic) isolated PV inverter with SPD to reduce impulse voltage for functional insulation	147
Figure I.3 – Isolated PV inverter with SPD to reduce impulse voltage for basic insulation	148

Figure I.4 – Transformer isolated auxiliary circuit with reinforced insulation	148
Figure I.5 – Transformerless PV inverter	149
Table 1 – Total temperature limits for transformers, inductors, and other coils and their	
insulation systems	30
Table 2 – Total temperature limits for materials and components where manufacturer's ratings and component standards do not exist (see 4.3.2.1)	30
Table 3 – Total touch temperature limits for accessible surfaces	31
Table 4 – Environmental categories, environmental conditions, and test requirements	45
Table 5 – Reduction of the pollution degree of internal environment through the use of additional protection	46
Table 6 – Summary of the limits of the decisive voltage classes	49
Table 7 – Examples of application of insulation and separation	50
Table 8 – Insulation between accessible unearthed parts and DVC-A or -B circuits adjacent to DVC-B or -C circuits	55
Table 9 – Values of accessible capacitance and charging voltage (threshold of pain)	59
Table 10 – Test duration for protective bonding test	65
Table 11 – External protective earthing conductor cross-section	66
Table 12 – Insulation voltage for low voltage circuits	71
Table 13 – Clearance distances	73
Table 14 – Creepage distances (mm)	75
Table 15 – Impulse voltage test	82
Table 16 – Impulse test voltage	83
Table 17 – AC or DC test voltage for circuits connected directly to the mains	84
Table 18 – a.c. or d.c. test voltage for circuits not connected directly to the mains	84
Table 19 – Partial discharge test	88
Table 20 – Summary of material flammability requirements	96
Table 21 – Allowable openings in fire enclosure bottoms	98
Table 22 – Limits for inherently limited power sources	101
Table 23 – Limits for power sources not inherently limited	101
Table 24 – Sizes of conductors	108
Table 25 – Physical tests on power supply cords	109
Table 26 – Wire bending space from terminals to obstructions	112
Table 27 – Minimum property retention limits after UV exposure	118
Table 28 – Thickness of sheet metal for enclosures: Carbon steel or stainless steel	121
Table 29 – Thickness of sheet metal for enclosures: aluminium, copper or brass	122
Table A.1 – Value of X	128
Table C.1 – Symbols	134
Table F.1 – Correction factor for clearances at altitudes above 2 000 m (see 7.3.7.4.1)	140
Table F.2 – Test voltages for verifying clearances at different altitudes	140
Table G.1 – Minimum values of clearances in air at atmospheric pressure for inhomogeneous field conditions (Table 1 of IEC 60664-4)	142
Table G.2 – Minimum values of creepage distances for different frequency ranges (Table 2 of IEC 60664-4)	115
ADIG & UL ILU UUUUT-T	14J