#### SRI LANKA STANDARD 1329:2017 (ISO 2439:2008) UDC 678.4

# METHOD OF TEST FOR THE DETERMINATION OF HARDNESS (INDENTATION TECHNIQUE) FOR FLEXIBLE CELLULAR POLYMERIC MATERIALS

(First Revision)

SRI LANKA STANDARDS INSTITUTION

# Sri Lanka Standard METHOD OF TEST FOR THE DETERMINATION OF HARDNESS (INDENTATION TECHNIQUE) FOR FLEXIBLE CELLULAR POLYMERIC MATERIALS (First Revision)

SLS 1329:2017 (ISO 2439:2008)

Gr.G

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
17, Victoria Place
Elvitigala Mawatha
Colombo 08
SRI LANKA.

## Sri Lanka Standard METHOD OF TEST FOR THE DETERMINATION OF HARDNESS (INDENTATION TECHNIQUE) FOR FLEXIBLE CELLULAR POLYMERIC MATERIALS (First Revision)

#### **FOREWORD**

This Sri Lanka Standard was approved by the Sectoral Committee on Chemical and Polymer Technology and was authorized for adoption and publication as a Sri Lanka Standard by the Council of the Sri Lanka Standards Institution on 2017-05-04.

This Sri Lanka Standard was first published in 2008 which was an adoption of 2439:1997 Flexible cellular polymeric materials - Determination of hardness (indentation technique). The International Standard ISO 2439: 1997 has been technically revised in 2008. ISO 2439: 2008 has been accepted to adopt as the first revision to **SLS 1329** to be referred for the determination of hardness of flexible polyurethane foam mattresses and cushions.

This Standard is identical with 2439 : 2008 Flexible cellular polymeric materials - Determination of hardness (indentation technique), published by the International Organization for Standardization (ISO).

#### **TERMINOLOGY AND CONVENTIONS:**

The text of the International Standard has been accepted as suitable for publication, without deviation, as a Sri Lanka Standard. However, certain terminology and conventions are not identical with those used in Sri Lanka Standards. Attention is therefore drawn to the following:

- a) Wherever the words 'International Standard' appear referring to a particular standard, they should be interpreted as "Sri Lanka Standard".
- b) The comma has been used throughout as a decimal marker. In Sri Lanka Standards it is the current practice to use the full point at the base as the decimal marker.
- c) Wherever page numbers are quoted, they are ISO page numbers.

SLS 1329:2017 (ISO 2439:2008)

#### **Cross References**

#### **International Standard**

#### Corresponding Sri Lanka Standard

ISO 1382 Rubber — Vocabulary

SLS 968 Glossary of terms used in the rubber industry

ISO 7500-1 Metallic materials — Verification of static uniaxial testing machines — Part 1: Tension/compression testing machines — Verification and calibration of the forcemeasuring system

No corresponding Sri Lanka Standard

preparing and conditioning test pieces for times for the conditioning and testing of physical test methods

ISO 23529 Rubber — General procedures for SLS 1323 Temperatures, humidities and rubber Part 1 General procedures for preparing and conditioning test pieces for physical test methods

.....

### INTERNATIONAL STANDARD

SLS 1329:2017 ISO 2439

Fourth edition 2008-12-15

### Flexible cellular polymeric materials — Determination of hardness (indentation technique)

Matériaux polymères alvéolaires souples — Détermination de la dureté (technique par indentation)



#### **Contents** Page

| Forewo  | ord   | iv  |
|---------|---|-----|
| 1       | Scope   | 1   |
| 2       | Normative references  | 1   |
| 3       | Terms and definitions   | . 2 |
| 4       | Principle   | 2   |
| 5       | Apparatus   | 2   |
| 6       | Test pieces   | . 3 |
| 6.1     | Shape and dimensions  | 3   |
| 6.2     | Samples showing orientation   | 3   |
| 6.3     | Conditioning  | . 3 |
| 7       | Procedure   | . 3 |
| 7.1     | General   | . 3 |
| 7.2     | Preliminary indentation for Methods A, B and C  | 4   |
| 7.3     | Method A — Determination of the 40 %/30 s indentation hardness index                        | . 4 |
| 7.4     | Method B — Determination of the 25 %-40 %-65 %/30 s indentation hardness characteristics    | 4   |
| 7.5     | Method C — Determination of the 40 % indentation hardness check                             | . 5 |
| 7.6     | Method D — Determination of the 25 %/20 s low indentation hardness index                    | . 5 |
| 7.7     | Method E — Determination of the compressive deflection coefficient and hysteresis loss rate | 5   |
| 8       | Repeat tests  | 7   |
| 9       | Test report   | . 7 |
| Annex   | A (informative) Test method parameters and typical graphs                                   | . 8 |
| Annex   | Annex B (informative) Precision of Method E   |     |
| Bibliog | Bibliography  |     |