

SRI LANKA STANDARD 1571: 2017
(IEC 60238: 2017)
UDC 621.3.032.82

**SPECIFICATION FOR
EDISON SCREW LAMPHOLDERS**

SRI LANKA STANDARDS INSTITUTION

Sri Lanka Standard
SPECIFICATION FOR EDISON SCREW LAMPHOLDERS

**SLS 1571: 2017
(IEC 60238: 2017)**

Gr. X

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
No, 17, Victoria Place
Elvitigala Mawatha
Colombo 08
SRI LANKA

Sri Lanka Standard
SPECIFICATION FOR EDISON SCREW LAMPHOLDERS

NATIONAL FOREWORD

This standard was approved by the Sectoral Committee on Electrical Appliances and Accessories and was authorized for adoption and publication as a Sri Lanka Standard by the Council of Sri Lanka Standards Institution on 2017-07-21

This Sri Lanka standard **SLS 1571 : 2017** is identical with **IEC 60238** 2017-01 incorporating Amd. No.1: 2017 Edition 9.1 Edison Screw Lampholders published by the International Electrotechnical Commission (IEC).

For the purpose of deciding whether a particular requirement of this standard is complied with the final value, observed or calculated, expressing the results of a test or an analysis shall be rounded off in accordance with **SLS 102**. The number of significant places to be retained in the rounded off value shall be the same as that of the specified value in the standard.

Terminology and conventions

The text of the International Standard has been accepted as suitable for publication without deviation as a Sri Lanka Standard. However, certain terminology and conventions are not identical with those used in Sri Lanka Standards; attention is therefore drawn to the following :

- a) Wherever the words “International Standard” appear referring to this standard they should be interpreted as “Sri Lanka Standard”.
- b) Wherever the page numbers are quoted they are the page numbers of IEC standard.
- c) The comma has been used as a decimal marker. In Sri Lanka Standards it is the current practices to use a full point on the base line as a decimal marker.
- d) Whenever standard value of rated frequency appears it shall be taken as 50 Hz.



CONSOLIDATED VERSION

VERSION CONSOLIDÉE



Edison screw lampholders

Douilles à vis edison pour lampes



CONTENTS

FOREWORD	4
1 Scope	6
2 Normative references	7
3 Terms and definitions	8
4 General requirement	13
5 General conditions for tests	13
6 Standard ratings	14
7 Classification	15
8 Marking	16
9 Dimensions	18
10 Protection against electric shock	21
11 Terminals	23
12 Provision for earthing	27
13 Construction	28
14 Switched lampholders	33
15 Moisture resistance, insulation resistance and electric strength	34
16 Mechanical strength	36
17 Screws, current-carrying parts and connections	40
18 Creepage distances and clearances	42
19 Normal operation	47
20 General resistance to heat	48
21 Resistance to heat, fire and tracking	50
22 Resistance to excessive residual stresses (season cracking) and to rusting	53
Annex A (normative) Season cracking/corrosion test	74
Annex B (informative) Guidance for requirements in IEC 61058-1 applicable to switches in lampholders (see 14.2)	76
Annex C (informative) Guidance for special requirements in appliance standards – Household and similar electrical appliances	78
Annex D (informative) Clauses containing new or more stringent requirements with respect to the previous edition	80
Bibliography	81
Figure 1a –Nipple thread for lampholders: metric thread. Basic profile and design profile for the nut and for the screw	54
Figure 1b –Nipple thread for lampholders: ISO standard pipe thread. Basic profile and design profile for the nut and for the screw	55
Figure 2a – Gauges for metric thread for nipples	56
Figure 2b – Gauges for ISO standard pipe thread for nipples	57
Figure 3 – Gauge for holes for backplate lampholder screws	58
Figure 4 – Normal operation test apparatus	59
Figure 5 – Test caps for the test of Clause 18	60
Figure 6 – Torque apparatus	61
Figure 7 – Tumbling barrel	62

Figure 8 – Impact-test apparatus	63
Figure 9 – Pressure apparatus	64
Figure 10 – Ball-pressure test apparatus	64
Figure 11 – Test cap for the tests of 15.4 and 20.3	65
Figure 12 – Bending apparatus	66
Figure 13 – Test cap A and test cap B for lampholders E14 (2 of 2)	68
Figure 14 – Test cap for lampholders E27	69
Figure 15 – Test cap for lampholders E40	70
Figure 16 – Standard test finger (according to IEC 60529)	71
Figure 17 – Clarification of some definitions	72
Figure 18 – Preparation of specimens for the needle-flame test of 21.4	73
Table 1 – Thickness of screw shells and contacts	19
Table 2 – Minimum effective screw lengths	20
Table 3 – Dimensions of threaded entries and set screws	21
Table 4 – Minimum dimensions of pillar-type terminals	25
Table 5 – Minimum dimensions of screw-type terminals	25
Table 6 – Pull and torque values	31
Table 7 – Insertion torque	33
Table 8 – Minimum and maximum removal torques	33
Table 9 – Test cap dimensions	37
Table 10 – Heights of fall	38
Table 11 – Maximum deformation values	40
Table 12 – Torque values	41
Table 13a – Minimum distances for AC sinusoidal voltages up to 30 kHz – Impulse withstand category II	44
Table 13b – Minimum distances for AC sinusoidal voltages up to 30 kHz – Impulse withstand category III	45
Table 14 – Minimum distances for ignition pulse voltages or equivalent peak voltages <i>Up</i>	46
Table 15 – Heating cabinet temperatures	49
Table A.1 – pH adjustment	74