

SRI LANKA STANDARD 555 : 1982

UDC 667.637



**SPECIFICATION FOR
VARNISH FOR INTERIOR USE**

BUREAU OF CEYLON STANDARDS

SPECIFICATION FOR VARNISH FOR INTERIOR USE

SLS 555:1982

Gr. 5

Copyright Reserved

BUREAU OF CEYLON STANDARDS

53, Dharmapala Mawatha,

Colombo 3,

Sri Lanka.

SRI LANKA STANDARD
SPECIFICATION FOR VARNISH FOR INTERIOR USE

FOREWORD

This Sri Lanka Standard was authorised for adoption and publication by the Council of the Bureau of Ceylon Standards on 1982-03-18 after the draft, finalized by the Drafting Committee on Paints had been approved by the Chemicals Divisional Committee.

This specification covers varnish, suitable for application where chemical resistance is not an important criterion.

All standard values in this specification are given in SI units.

For the purpose of deciding whether a particular requirement of this specification is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with CS 102. The number of significant places retained in the rounded off value should be the same as that of the specified value in this specification.

In the preparation of this specification, the assistance obtained from the publications of the Indian Standards Institution is gratefully acknowledged.

1 SCOPE

This specification prescribes requirements and methods of sampling and test for the material commercially known as varnish, finishing, interior. The material is used for the protection and decoration of interior work generally on wooden surfaces.

2 REFERENCES

- CS 102 Presentation of numerical values
- CS 159 Code of practice for seasoning timber
- SLS 489 Glossary of terms for paints
- SLS 523 Methods of sampling paints
- SLS 535 Methods of test for paints