SRI LANKA STANDARD 1207: Part 1: 2001

UDC 685.555

SPECIFICATION FOR UMBRELLA PART 1: NON FOLDING UMBRELLA

SRI LANKA STANDARDS INSTITUTION

SRI LANKA STANDARD SPECIFICATION FOR UMBRELLA PART 1: NON-FOLDING UMBRELLA

SLS 1207 Part 1:2001

(Attached AMD 377)

Gr. 4

Sri Lanka Standards Institution No. 17, Victoria Place, Elvitigala Mawatha, Colombo - 08, Sri Lanka. Sri Lanka Standards are subject to periodical revision in order to accommodate the progress made by industry. Suggestions for improvement will be recorded and brought to the notice of the Committees to which the revisions are entrusted.

This standard does not purport to include all the necessary provisions of a contract.

© SLSI 2001

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the SLSI.

SRI LANKA STANDARD SPECIFICATION FOR UMBRELLA PART 1: NON-FOLDING UMBRELLA

FOREWORD

This standard was approved by the Sectoral Committee on Textiles, Clothing and Leather and was authorized for adoption and publication as a Sri Lanka Standard by the Council of the Sri Lanka Standards Institution on 2001-02-08.

Umbrella is a widely used consumer item that needs to be standardized for the benefit of both the consumer and manufacturer. This standard consists of two parts:

Part 1 : Non-folding Umbrella Part 2 : Folding Umbrella

For the purpose of deciding whether a particular requirement of this specification is complied with, the final value, observed or calculated, expressing the result of a test or an analysis shall be rounded off in accordance with **CS 102.** The number of significant places retained in the rounded off value shall be the same as that of the specified value in this specification.

Guidelines for the determination of a compliance of a lot with the requirements of this standard based on statistical sampling and inspection are given in Appendix A.

In the preparation of this standard the assistance derived from the following publication is gratefully acknowledged:

IS 2920: 1979 (1992) Indian Standard Specification for Umbrellas.

1 SCOPE

This specification prescribes the requirements for non-folding umbrella. It does not cover toy, hat and garden umbrella.

2 REFERENCES

CS 102: Presentation of numerical values

CS 195 : Cotton umbrella cloth

SLS 321: Umbrella ribs

SLS 428: Random sampling methods

SLS 445: Umbrella fittings

SLS 757: Polyester sewing thread SLS 1160: Nylon umbrella cloth

3 TYPES

Umbrella shall be of following types depending on the size, expressed as the length of main ribs.

Туре	Minimum length of main ribs	
Gents	533 mm	(21) *
Ladies	457 mm	(18)
Children	356 mm	(14)

^{*} Values given in brackets are approximate inch values.

4 REQUIREMENTS

4.1 Components (See Figure 1)




FIGURE 1 - Diagram of Non-Folding Umbrella

SLS 1207 Part 1: 2001

- **4.1.1** The main ribs and stretcher ribs used shall conform to SLS 321.
- **4.1.2** The runner, notch, cap and ferrule used shall conform to SLS 445.
- **4.1.3** The cloth used shall conform to **CS 195** or **SLS 1160**.

4.2 Workmanship

4.2.1 The minimum number of main ribs or pairs of main ribs (in case of double rib umbrellas) in an umbrella shall be six. In the case of rectangular umbrellas the minimum number of main ribs shall be four.

The horizontal distance (D) from mid of the panel to stick (see Figure 1) shall be not less than 85 per cent of the length of the main rib (R).

- **4.2.2** The notch shall be rigidly and firmly fixed on the tube or stick. The ribs shall be fastened on the notch by means of brass, copper or galvanized wire of 1 mm diameter so that ribs have no undue play or shake. The ends of the wire shall be turned in so that they do not touch the cloth of the umbrella.
- **4.2.3** The stretcher ribs shall be firmly attached to the runner by means of brass, copper or galvanized wire of 1 mm diameter. The runner shall be capable of being held at the upper stopper when the umbrella is opened.
- **4.2.4** The handle shall be fixed to the tube in such a manner that when the handle is subjected to a pull of 100 N for one minute, it shall not break or get detached from the tube.

NOTE

This test is not applicable to umbrella with sticks.

4.2.5 The cloth shall be suitably cut in panels and firmly stitched together by strong sewing thread conforming to Ticket Number 120 or better of Table 1 of SLS 757: 1993. Colour fastness of the thread to washing and light shall conform to Table 2 of SLS 757: 1993. The shade of the thread shall be as agreed to between the buyer and seller. The minimum number of stitches per 10 mm shall be four.

NOTE

In the event of seeking a test certificate on umbrella, it is adviced to produce a sample of threads used for stitching along with the umbrella sample.

Edge of umbrella cloth shall be of natural border (selvedged) or stitched. If stitched, the minimum number of stitches per 25 mm shall be four.

- **4.2.6** The cloth shall be stitched firmly to the holes at the ends of the ribs with a minimum of five stitches including tieing stitches and also suitably stitched at the junction of the main ribs and stretcher ribs. At the top, the cloth shall be bound five times and so stitched as to have one stitch per panel and two extra stitches for final tieing. The thread used shall conform to Ticket Number 50 or better of **SLS 757** or an equivalent nylon thread. Shade and colour fastness requirements shall be as in **4.2.5** (See Note under **4.2.5**).
- **4.2.7** A plastic or cloth piece shall be placed at the top above the notch and under the cloth. A plastic or waterproof cloth known as *chandwa* may be fitted over the cloth, under the cap.
- **4.2.8** The seams shall not yield or bulge and the cloth shall not be slack or show any other defect when the umbrella is fully opened. The stitching thread shall not be visible on the outer surface.
- **4.2.9** The umbrella cloth shall be provided with a band with suitable means for wrapping the cloth when the umbrella is closed.
- **4.2.10** The cap shall be firmly fixed to prevent rain water from seeping.
- **4.2.11** The assembly of the cup on the handle shall be such that the cup is able to hold the ball ends of all the main ribs, when the umbrella is in closed position. The cup shall be such as not to allow the rib ends to be released, unless it is pulled to its extreme position.
- **4.2.12** After opening and closing the umbrella 50 times in an uniform manner, the ribs shall not show any deformation and the cloth shall not show any signs of opening at seams or bulging. The umbrella shall be capable of being opened and closed smoothly without the runner getting stuck. When opened, the umbrella shall have a symmetrical shape. In the case of flexus ribs, the umbrella shall close automatically when the stopper is pressed.

5 PACKAGING

Each umbrella shall be suitably packed as agreed to between the purchaser and the supplier. Six to twelve umbrellas shall be packed in a bundle.

SLS 1207 Part 1: 2001

6 MARKING

Each umbrella and bundle of umbrella shall be marked or labelled with the following:

- a) Type and/or size of umbrella;
- b) Name and contact number of the manufacturer;
- c) Registered trade mark, if any; and
- d) Batch/code number.

NOTE

Attention is drawn to the certification marking facilities offered by the Sri Lanka Standards Institution. See the inside back cover of the standard.

APPENDIX A COMPLIANCE OF A LOT

The sampling scheme given in this Appendix should be applied where compliance of a lot to the requirements of this standard is to be assessed based on statistical sampling and inspection.

Where compliance with this standard is to be assured based on manufacturing control system coupled with type testing and check tests of any other procedure, appropriate schemes of sampling and inspection should be adopted.

A.1 LOT

In any consignment all umbrella of same type and size belonging to one batch of manufacture or supply shall constitute a lot.

A.2 SCALE OF SAMPLING

A.2.1 Number of umbrellas to be selected from a lot shall be in accordance with Table 1.

SLS 1207 Part 1: 2001

TABLE 1 - Scale of sampling

Number of umbrellas in the lot	Number of umbrellas to be selected
Up to 150	05
151 - 250	08
251 - 500	10
501 and above	13

A.2.2 Umbrellas shall be selected at random. In order to ensure randomness of selection random number tables as given in **SLS 428** shall be used.

A.3 NUMBER OF TESTS

- **A.3.1** Each umbrella selected as in **A.2.1** shall be inspected for marking and packaging requirements.
- **A.3.2** Each umbrella selected as in **A.2.1** shall be inspected for requirements in **4.2.**

A.4 CRITERIA FOR CONFORMITY

A lot shall be declared as conforming to the requirements of this specification if the following conditions are satisfied:

- **A.4.1** Each umbrella inspected as **A.3.1** satisfies the marking and packaging requirements.
- **A.4.2** Each umbrella inspected **A.3.2** satisfies the relevant requirements.

AMENDMENT NO:1 TO SLS 1207:PART 1:2001

SPECIFICATION FOR UMBRELLA PART 1: NON FOLDING UMBRELLA

EXPLANATORY NOTE

In the existing Sri Lanka Standard SLS 1207 Specification for umbrella, which consists of two parts, in part 1 the specified minimum number of stitches of the edge of the umbrella cloth is four per 25 mm where as in part 2 it is given as eight per 25 mm, which is the correct limit.

Also in the existing standard it is a requirement that the umbrella cloth shall confirm to CS 195 and SLS 1160. Both these standards are superseded by SLS 1307.

Therefore this amendment is issued to change the number of stitches of the edge of the umbrella cloth and to replace CS 195 and SLS 1160 by SLS 1307 in the appropriate clauses.

AMENDMENT NO:1 APPROVED ON 2008-12-19 TO SLS 1207 SPECIFICATION FOR UMBRELLA

PART 1:2001 NON FOLDING UMBRELLA.

Page 3

Clause 2 REFERENCES

Delete "CS 195 Cotton umbrella cloth" and "SLS 1160 Nylon umbrella cloth" and insert "SLS 1307 Woven umbrella cloth".

Page 5

4.1.3

Delete "CS 195 or SLS 1160" and insert "SLS 1307"

4.2.5

2nd paragraph

Line 2

Delete "stitches per 25 mm shall be four" and insert "stitches per 25 mm shall be eight".

SRI LANKA STANDARDS INSTITUTION

The Sri Lanka Standards Institution (SLSI) is the National Standards Organization of Sri Lanka established under the Sri Lanka Standards Institution Act No. 6 of 1984 which repealed and replaced the Bureau of Ceylon Standards Act No. 38 of 1964. The Institution functions under the Ministry of Science & Technology.

The principal objects of the Institution as set out in the Act are to prepare standards and promote their adoption, to provide facilities for examination and testing of products, to operate a Certification Marks Scheme, to certify the quality of products meant for local consumption or exports and to promote standardization and quality control by educational, consultancy and research activity.

The Institution is financed by Government grants, and by the income from the sale of its publications and other services offered for Industry and Business Sector. Financial and administrative control is vested in a Council appointed in accordance with the provisions of the Act.

The development and formulation of National Standards is carried out by Technical Experts and representatives of other interest groups, assisted by the permanent officers of the Institution. These Technical Committees are appointed under the purview of the Sectoral Committees which in turn are appointed by the Council. The Sectoral Committees give the final Technical approval for the Draft National Standards prior to the approval by the Council of the SLSI.

All members of the Technical and Sectoral Committees render their services in an honorary capacity. In this process the Institution endeavours to ensure adequate representation of all view points.

In the International field the Institution represents Sri Lanka in the International Organization for Standardization (ISO), and participates in such fields of standardization as are of special interest to Sri Lanka.

Printed at the Sri Lanka Standards Institution, 17, Victoria Place, Elvitigala Mawatha, Colombo 08.

SLS CERTIFICATION MARK

The Sri Lanka Standards Institution is the owner of the registered certification mark shown below. Beneath the mark, the number of the Sri Lanka Standard relevant to the product is indicated. This mark may be used only by those who have obtained permits under the SLS certification marks scheme. The presence of this mark on or in relation to a product conveys the assurance that they have been produced to comply with the requirements of the relevant Sri Lanka Standard under a well designed system of quality control inspection and testing operated by the manufacturer and supervised by the SLSI which includes surveillance inspection of the factory, testing of both factory and market samples.

Further particulars of the terms and conditions of the permit may be obtained from the Sri Lanka Standards Institution, 17, Victoria Place, Elvitigala Mawatha, Colombo 08.

