### SRI LANKA STANDARD 735 Part 19: 2019 (ISO 14156: 2001) UDC 637.1

## METHODS OF TEST FOR MILK AND MILK PRODUCTS PART 19: EXTRACTION METHODS FOR LIPIDS AND LIPOSOLUBLE COMPOUNDS

SRI LANKA STANDARDS INSTITUTION

# Sri Lanka Standard METHODS OF TEST FOR MILK AND MILK PRODUCTS PART 19: EXTRACTION METHODS FOR LIPIDS AND LIPOSOLUBLE COMPOUNDS

SLS 735 Part 19: 2019 (ISO 14156: 2001)

Gr. C

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
17, Victoria Place
Elvitigala Mawatha
Colombo 08
Sri Lanka

Sri Lanka Standards are subject to periodical revision in order to accommodate the progress made by industry. Suggestions for improvement will be recorded and brought to the notice of the Committees to which the revisions are entrusted.

This Standard does not purport to include all the necessary provisions of a contract

- © ISO 2001 All right reserved.
- © SLSI 2019

All right reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the SLSI.

SLS 735 Part 19: 2019 (ISO 14156: 2001)

# Sri Lanka Standard METHODS OF TEST FOR MILK AND MILK PRODUCTS EXTRACTION METHODS FOR LIPIDS AND LIPOSOLUBLE COMPOUNDS

#### NATIONAL FOREWORD

This Standard was authorized for adoption and publication by the Council of the Sri Lanka Standards Institution on 2019-08-07.

This Sri Lanka Standard is identical with **ISO 14156: 2001** Milk and milk products-Extraction methods for lipids and liposoluble compounds published by the International Organization for Standardization (ISO).

This Standard provides general requirements for the competence and consistent operation of reference material producers.

#### **Terminology and conventions:**

The text of the International Standard has been accepted as suitable for publication, without deviation, as a Sri Lanka Standard. However, certain terminology and conventions are not identical with those used in Sri Lanka Standards. Attention is therefore drawn to the following:

- a) Wherever the words "International Standard" appear referring to this Standard, it should be interpreted as "Sri Lanka Standard".
- b) The comma has been used throughout as a decimal marker. In Sri Lanka Standards it is the current practice to use the full point on the base line as the decimal marker.
- c) Wherever page numbers are quoted, they are ISO page numbers.

.....

# INTERNATIONAL STANDARD

ISO 14156

**IDF** 172

First edition 2001-12-01

# Milk and milk products — Extraction methods for lipids and liposoluble compounds

Lait et produits laitiers — Méthodes d'extraction des lipides et des composés liposolubles



SLS 735 PART 19: 2019 ISO 14156 :2001(E) IDF 172:2001(E)

#### **PDF** disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. Neither the ISO Central Secretariat nor the IDF accepts any liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies and IDF national committees. In the unlikely event that a problem relating to it is found, please inform the ISO Central Secretariat at the address given below.

#### © ISO and IDF 2001

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO or IDF at the respective address below.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

International Dairy Federation
41 Square Vergote • B-1030 Brussels
Tel. + 322 733 98 88
Fax + 322 733 04 13
E-mail info@fil-idf.org

Web www.fil-idf.org

SLS 735 PART 19: 2019 ISO 14156 :2001(E) IDF 172:2001(E)

#### **Foreword**

**ISO** (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 14156|IDF 172 was prepared by Technical Committee ISO/TC 34, *Food products*, Subcommittee SC 5, *Milk and milk products*, and the International Dairy Federation (IDF), in collaboration with AOAC International. It is being published jointly by ISO and IDF and separately by AOAC International.

© ISO 2001 – All rights reserved iii

SLS 735 PART 19: 2019 ISO 14156 :2001(E) IDF 172:2001(E)

#### **Foreword**

**IDF (the International Dairy Federation)** is a worldwide federation of the dairy sector with a National Committee in every member country. Every National Committee has the right to be represented on the IDF Standing Committees carrying out the technical work. IDF collaborates with ISO and AOAC International in the development of standard methods of analysis and sampling for milk and milk products.

Draft International Standards adopted by the Action Teams and Standing Committees are circulated to the National Committees for voting. Publication as an International Standard requires approval by at least 50 % of National Committees casting a vote.

International Standard ISO 14156|IDF 172 was prepared by Technical Committee ISO/TC 34, *Food products*, Subcommittee SC 5, *Milk and milk products*, and the International Dairy Federation (IDF), in collaboration with AOAC International. It is being published jointly by ISO and IDF and separately by AOAC International.

All work was carried out by the Joint ISO/IDF/AOAC Action Team, *Fat*, under the aegis of its project leader, Mr R.J. de Knegt (NL).

ISO 14156 :2001(E) IDF 172:2001(E)

## Milk and milk products — Extraction methods for lipids and liposoluble compounds

#### 1 Scope

This International Standard specifies methods for the extraction or separation of a representative part of the fat, containing lipids and liposoluble compounds, from milk and milk products.

The method is applicable to pretreatment of samples for the methods described in ISO 15884 and ISO 15885.

It should be noted that free fatty acids are not part of extracted fat as described in methods for the fat determination in milk, condensed milk, dried milk products, cream and fermented milk.

#### 2 Term and definition

For the purposes of this International Standard, the following term and definition apply.

#### 2.1

#### lipids and liposoluble compounds

substances extracted or separated by the various procedures specified in this International Standard

#### 3 Principle

The lipids and liposoluble compounds of milk and various milk products are extracted or separated for further analysis. In the case of butter and other high-fat products, the lipid fraction is physically separated. For other products, the lipids and related compounds are extracted with solvents after suitable preparation of the sample.

#### 4 Reagents

Use only reagents of recognized analytical grade, unless otherwise specified, and distilled or demineralized water free from chloride, or water of equivalent purity.

- **4.1** Ammonia solution,  $c(NH_3) = 14 \text{ mol/l} \ (\rho_{20} = 919 \text{ g/l}).$
- **4.2 Ethanol** ( $C_2H_5OH$ ), containing a volume fraction of 96 %  $\pm$  2 %.
- **4.3** Diethyl ether  $(C_2H_5OC_2H_5)$ , free from peroxides.
- 4.4 Anyhdrous sodium sulfate (Na<sub>2</sub>SO<sub>4</sub>).
- 4.5 Sodium sulfate solution.

Dissolve 100 g of anhydrous sodium sulfate (Na<sub>2</sub>SO<sub>4</sub>) in water. Dilute to 1 litre with water.

- 4.6 *n*-Pentane.
- **4.7 Sand**, free from organic material.

#### 5 Apparatus

Usual laboratory equipment and, in particular, the following.

- **5.1** Oven, capable of being maintained at a temperature of 50  $^{\circ}$ C  $\pm$  5  $^{\circ}$ C.
- **5.2 Soxhlet extraction apparatus**, provided with an extraction thimble.
- **5.3** Water baths, capable of being maintained at temperatures of between 40 °C and 60 °C, 30 °C and 40 °C, and 50 °C  $\pm$  2 °C.
- **5.4** Separating funnel, of capacity 500 ml.
- **5.5 Measuring cylinders**, of capacities 100 ml and 250 ml.
- **5.6** Beakers, of capacity 100 ml.
- **5.7 Filter paper**, medium porosity, of diameter about 15 cm.
- **5.8** Conical flask, of capacity 250 ml.
- **5.9** Round-bottom flask, of capacity 250 ml.
- **5.10** Rotary evaporator, with accessories.
- 5.11 Spoon or spatula.

#### 6 Sampling

Sampling is not part of the method specified in this International Standard. A recommended sampling method is given in ISO 707.

It is important that the laboratory receive a sample which is truly representative and has not been damaged or changed during transport or storage.

Store the sample in such a way that deterioration and change in its composition are prevented.

#### 7 Preparation of test sample

#### 7.1 Raw milk and raw cream

Bring the test sample in a water bath (5.3) to a temperature of 35 °C to 40 °C. Mix the sample by repeated inversion, then cool it quickly to 20 °C  $\pm$  2 °C.

#### 7.2 Homogenized milk, homogenized cream and fermented milk

Bring the test sample to a temperature of 20 °C  $\pm$  2 °C. Mix or stir the sample thoroughly.

#### 7.3 Evaporated milk

Shake and invert the container. Open the container, pour the test sample slowly into a second container (provided with an airtight lid) and mix by repeated transfer, taking care to incorporate in the sample any fat or other constituent adhering to the wall of the first container. Finally, transfer the milk as completely as possible to the second container. Close the container.

In the case of samples in sealed cans, condition the unopened can in a water bath (5.3) set at a temperature of between 40 °C and 60 °C, if necessary. Shake the can vigorously every 15 min. After 2 h, remove the can from the water bath and allow the can and its contents to cool to room temperature. Remove the lid and thoroughly mix the contents of the can by stirring with a spoon or spatula (5.11).

#### 7.4 Sweetened condensed milk

Open the sample container and thoroughly mix the test sample with a spoon or spatula. Use an up and down rotary movement in such a way that the top layer and the contents of the lower corners of the container are moved and mixed. Take care to incorporate in the sample all milk adhering to the wall of the container. Transfer the test sample as completely as possible to a second container (provided with an airtight lid). Close this container.

In the case of samples in sealed cans, condition the unopened can in a water bath (5.3) set at a temperature of between 30 °C and 40 °C, if necessary. Open the can and transfer the complete test sample, by scraping out all the sample adhering to the interior of the can, into a dish which is large enough to permit thorough stirring. Mix the contents of the dish until the mass is homogeneous.

In the case of a test sample in a collapsible tube, open the tube and transfer its contents to a jar. Cut open the tube, scrape out all test sample adhering to the interior of the tube, and add that to the contents of the jar too. Mix the contents of the jar until the mass is homogeneous.

#### 7.5 Dried milk products

Thoroughly mix the test sample by repeatedly rotating and inverting the container.

#### 7.6 Cheese

Before analysis, remove the rind or any smear or mouldly surface layer of the cheese so as to give a test sample representative of the cheese as it is usually consumed.

#### 8 Procedure

#### 8.1 General

For test samples with a relatively high content of phospholipids and a relatively low content of simple lipids (e.g. buttermilk), the chosen extraction procedure will affect the fatty acid composition of the extracted fat. For these test samples the procedure described in 8.3 and the addition of approximately 1,5 g of sodium chloride to the test portion is recommended. The fat thus extracted will contain the phospholipids. The fatty acid composition of the phospholipids differs considerably from that of the other milk fat components.

#### 8.2 Anhydrous milk fat, butteroil and butter

Melt 50 g to 100 g of test sample in the oven (5.1) set at a temperature of 50 °C. Place 0,5 g to 1,0 g of anhydrous sodium sulfate (4.4) in a folded filter paper. Filter the fat through the filter paper containing anhydrous sodium sulfate collecting the filtrate in a beaker (5.6) maintained in the oven (5.1) set at a temperature of 50 °C. When decanting the melted butter onto the filter paper (5.7), take care that no serum is transferred.

#### 8.3 Raw milk and homogenized milk

Mix 100 ml of the test sample with 80 ml of ethanol (4.2) and 20 ml of ammonia solution (4.1) in a separating funnel (5.4).

Add 100 ml of diethyl ether (4.3) and shake the funnel vigorously for 1 min. Let it stand to achieve phase separation. Then add 100 ml of n-pentane (4.6) to the contents of the funnel and mix carefully. Let the funnel stand for a second phase separation, then discard the aqueous layer.

SLS 735 PART 19: 2019 ISO 14156 :2001(E) IDF 172:2001(E)

Add 100 ml of sodium sulfate solution (4.5) to the remaining contents of the funnel and mix carefully again. Let the funnel stand for a third phase separation and thereafter discard the aqueous layer. Add a second amount of 100 ml of the sodium sulfate solution to the remaining contents of the funnel and shake vigorously for 1 min. Let the funnel stand for phase separation and discard the aqueous layer again. Transfer the remaining organic layer to a conical flask (5.8). Add 5 g to 10 g of anhydrous sodium sulfate (4.4), stopper the flask and mix the contents of the flask.

Allow the flask to stand for 10 min and filter its contents into a round-bottom flask (5.9). Using the rotary evaporator (5.10), evaporate the contents of the flask under reduced pressure in a water bath (5.3) set at 50 °C until evaporation is visually completed.

Disconnect the flask from the rotary evaporator. Flush the flask contents with a stream of nitrogen for 1 min. Again connect the flask to the evaporator and continue evaporation for another period of 10 min. Despite this second evaporation step, the evaporation of the solvent will not be complete. The solvent residue will have a mass fraction of less than 2 %.

For some analyses of fat (e.g. fatty acid composition) complete removal of the solvent is not necessary. If, however, complete removal of the solvent is necessary, heat the contents of the flask in an oven set at 102 °C until a constant mass is obtained.

CAUTION — It should be noted that at a temperature of 102 °C decomposition of the fat (e.g. linolenic acid), or of other components of the fat, might occur.

Note that the fat extracted as above does not contain the free fatty acids.

#### 8.4 Sweetened condensed milk, evaporated milk, cream and fermented milk

Dilute a suitable amount of test sample so as to obtain about 100 ml of test portion with a mass fraction of fat of approximately 4 %. Proceed as in 8.3.

#### 8.5 Dried milk products

Prepare a test portion by reconstituting 10 g of the test sample in 100 ml of distilled water. Place the test portion in a water bath (5.3) set at 60 °C for 30 min, with shaking from time to time. Cool to room temperature and proceed as in 8.3.

#### 8.6 Cheese

Grate or mash the cheese depending on its texture.

Transfer an amount of test sample containing approximately 4 g of fat into a mortar. Grind the sample well with a 1 + 1 mixture of sand (4.7) and sodium sulfate (4.4) to yield a dry test sample.

NOTE The amount of sodium sulfate/sand mixture required depends on the water content of the cheese.

Transfer the complete test portion into the extraction thimble and insert the latter (closed, for example, by a cotton wool plug) into the chamber of the Soxhlet extraction apparatus (5.2). Fill the round-bottom flask with 250 ml of n-pentane (4.6) and extract the sample for 6 h under reflux.

Using the rotary evaporator (5.10), evaporate the contents of the flask under reduced pressure in a water bath (5.3) set at 50 °C until evaporation is visually completed.

Disconnect the flask and flush its contents with a stream of nitrogen for 1 min. Connect the flask again to the rotary evaporator and continue evaporation for another period of 10 min. (See also CAUTION in 8.3.)

#### 9 Report

The report shall specify:

- all information necessary for the complete identification of the sample;
- the sampling method used, if known;
- the extraction method used, together with reference to this International Standard;
- all operating details not specified in this International Standard, or regarded as optional, together with details of any incidents which may have influenced the result.

### **Bibliography**

- [1] ISO 707, Milk and milk products Guidance on sampling
- [2] ISO 15884, Milk fat Preparation of fatty acid methyl esters
- [3] ISO 15885, Milk fat Determination of the fatty acid composition by gas-liquid chromatography

SLS 735 PART 19: 2019

ISO 14156 :2001(E) IDF 172:2001(E)

Price based on 6 pages

### SLS CERTIFICATION MARK

The Sri Lanka Standards Institution is the owner of the registered certification mark shown below. Beneath the mark, the number of the Sri Lanka Standard relevant to the product is indicated. This mark may be used only by those who have obtained permits under the SLS certification marks scheme. The presence of this mark on or in relation to a product conveys the assurance that they have been produced to comply with the requirements of the relevant Sri Lanka Standard under a well designed system of quality control inspection and testing operated by the manufacturer and supervised by the SLSI which includes surveillance inspection of the factory, testing of both factory and market samples.

Further particulars of the terms and conditions of the permit may be obtained from the Sri Lanka Standards Institution, 17, Victoria Place, Elvitigala Mawatha, Colombo 08.



#### SRI LANKA STANDARDS INSTITUTION

The Sri Lanka Standards Institution (SLSI) is the National Standards Organization of Sri Lanka established under the Sri Lanka Standards Institution Act No. 6 of 1984 which repealed and replaced the Bureau of Ceylon Standards Act No. 38 of 1964. The Institution functions under the Ministry of Science & Technology.

The principal objects of the Institution as set out in the Act are to prepare standards and promote their adoption, to provide facilities for examination and testing of products, to operate a Certification Marks Scheme, to certify the quality of products meant for local consumption or exports and to promote standardization and quality control by educational, consultancy and research activity.

The Institution is financed by Government grants, and by the income from the sale of its publications and other services offered for Industry and Business Sector. Financial and administrative control is vested in a Council appointed in accordance with the provisions of the Act.

The development and formulation of National Standards is carried out by Technical Experts and representatives of other interest groups, assisted by the permanent officers of the Institution. These Technical Committees are appointed under the purview of the Sectoral Committees which in turn are appointed by the Council. The Sectoral Committees give the final Technical approval for the Draft National Standards prior to the approval by the Council of the SLSI.

All members of the Technical and Sectoral Committees render their services in an honorary capacity. In this process the Institution endeavours to ensure adequate representation of all view points.

In the International field the Institution represents Sri Lanka in the International Organization for Standardization (ISO), and participates in such fields of standardization as are of special interest to Sri Lanka.

Printed at the Sri Lanka Standards Institution, 17, Victoria Place, Elvitigala Mawatha, Colombo 08.