

SRI LANKA STANDARDS 1198 PART 1: 2022
(IEC 60086-1:2021)
UDC 621.352

**SPECIFICATION FOR
PRIMARY CELLS AND BATTERIES**
Part 1 General Requirements
(Third Revision)

SRI LANKA STANDARDS INSTITUTION

**Specification for
PRIMARY CELLS AND BATTERIES
Part 1 General Requirements
(*Third Revision*)**

**SLS 1198 Part 1: 2022
(IEC 60086-1:2021)**

Gr. T

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
No. 17, Victoria Place,
Elvitigala Mawatha,
Colombo 08.
SRI LANKA

Sri Lanka Standard
PRIMARY CELLS AND BATTERIES
Part 1 General Requirements
(Third Revision)

NATIONAL FOREWORD

This standard was approved by the Sectoral Committee on Electrical Appliances and Accessories and was authorized for adoption and publication as a Sri Lanka Standard by the Council of Sri Lanka Standards Institution on 2022-02-21

This is the Second Revision of **SLS 1198: Part 1** and is identical with **IEC 60086-1: 2021-04** Edition 13.0 Primary Cells Part 1: General published by the International Electrotechnical Commission (IEC).

For the purpose of deciding whether a particular requirement of this standard is complied with the final value, observed or calculated, expressing the results of a test or an analysis shall be rounded off in accordance with **SLS 102**. The number of significant places to be retained in the rounded off value shall be the same as that of the specified value in the standard.

Terminology and conventions

The text of the International Standard has been accepted as suitable for publication without deviation, as a Sri Lanka Standard. However, certain terminology and conventions are not identical with those used in Sri Lanka Standards; attention is therefore drawn to the following:

- a) Wherever the words “International Standard” appear referring to this standard they should be interpreted as “Sri Lanka Standard”.
- b) Wherever the page numbers are quoted they are the page numbers of IEC standard.
- c) The comma has been used as a decimal marker. In Sri Lanka Standards it is the current practices to use a full point on the base line as a decimal marker.
- d) Whenever standard value of rated frequency appears it shall be taken as 50 Hz.



INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Primary batteries –
Part 1: General**

**Piles électriques –
Partie 1: Généralités**





INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Primary batteries –
Part 1: General**

**Piles électriques –
Partie 1: Généralités**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD	5
INTRODUCTION	7
1 Scope	8
2 Normative references	8
3 Terms and definitions	8
4 Requirements	11
4.1 General	11
4.1.1 Design	11
4.1.2 Battery dimensions	11
4.1.3 Terminals	11
4.1.4 Classification (electrochemical system)	13
4.1.5 Designation	14
4.1.6 Marking	14
4.1.7 Interchangeability: battery voltage	15
4.2 Performance	16
4.2.1 Discharge performance	16
4.2.2 Dimensional stability	16
4.2.3 Leakage	16
4.2.4 Open-circuit voltage limits	16
4.2.5 Service output	16
4.2.6 Safety	16
4.2.7 Validity of testing	17
5 Performance – Testing	17
5.1 Capacity testing versus application and service output testing	17
5.2 Discharge testing	17
5.2.1 General	17
5.2.2 Application tests	18
5.2.3 Service output tests	18
5.3 Conformance check to a specified minimum average duration	19
5.4 Guidance for considering proposed value of minimum average duration	19
5.5 OCV testing	19
5.6 Insulation resistance	19
5.7 Battery dimensions	19
5.8 Leakage and deformation	19
6 Performance – Test conditions	20
6.1 Storage and discharge conditions	20
6.2 Commencement of discharge tests after storage	20
6.3 Discharge test conditions	20
6.3.1 General	20
6.3.2 Compliance	20
6.4 Load resistance	21
6.5 Time periods	21
6.6 Test condition tolerances	21
6.7 Activation of 'P'-system batteries	21
6.8 Measuring equipment	22
6.8.1 Voltage measurement	22

6.8.2	Mechanical measurement	22
7	Sampling and quality assurance	22
8	Battery packaging	22
	Annex A (normative) Criteria for the standardization of batteries	23
	Annex B (informative) Recommendations for equipment design	24
B.1	Technical liaison	24
B.2	Battery compartment	24
B.2.1	General	24
B.2.2	Limiting access by children	25
B.3	Voltage cut-off	25
	Annex C (normative) Designation system (nomenclature)	26
C.1	General	26
C.2	Designation system in use up to October 1990	26
C.2.1	General	26
C.2.2	Cells	26
C.2.3	Electrochemical system	28
C.2.4	Batteries	28
C.2.5	Modifiers	29
C.2.6	Examples	29
C.3	Designation system in use since October 1990	29
C.3.1	General	29
C.3.2	Round batteries	29
C.3.3	Non-round batteries	33
C.3.4	Ambiguity	36
	Annex D (informative) Standard discharge voltage U_S – Definition and method of determination	38
D.1	Definition	38
D.2	Determination	38
D.2.1	General considerations: the C/R -plot	38
D.2.2	Determination of the standard discharge resistor R_S	39
D.2.3	Determination of the standard discharge capacity C_S and standard discharge time t_S	40
D.3	Experimental conditions to be observed and test results	41
	Annex E (informative) Preparation of standard methods of measuring performance (SMMP) of consumer goods	42
E.1	General	42
E.2	Performance characteristics	42
E.3	Criteria for the development of test methods	42
	Annex F (informative) Guidance for proposing value of minimum average duration	43
F.1	General	43
F.2	Sampling	43
F.3	Calculation method	43
	Annex G (normative) Code of practice for packaging, shipment, storage, use and disposal of primary batteries	44
G.1	General	44
G.2	Packaging	44
G.3	Transport and handling	44
G.4	Storage and stock rotation	44

G.5	Displays at sales points	45
G.6	Selection, use and disposal	45
G.6.1	Purchase	45
G.6.2	Installation.....	45
G.6.3	Use.....	45
G.6.4	Replacement	46
G.6.5	Disposal	46
Annex H (informative)	Compliance checklist	47
Bibliography.....		48
Figure C.1	– Designation system for round batteries: $d_1 < 100$ mm; height $h_1 < 100$ mm	30
Figure C.2	– Diameter code for non-recommended diameters	31
Figure C.3	– Height code for denoting the hundredths of a millimetre of height	32
Figure C.4	– Designation system for round batteries: $d_1 \geq 100$ mm; height $h_1 \geq 100$ mm	33
Figure C.5	– Designation system for non-round batteries, dimensions < 100 mm	34
Figure C.6	– Designation system for non-round batteries, dimensions ≥ 100 mm	35
Figure C.7	– Height code for discrimination per tenth of a millimetre	35
Figure D.1	– Normalized C/R-plot (schematic)	39
Figure D.2	– Standard discharge voltage (schematic)	40
Table 1	– Standardized electrochemical systems	13
Table 2	– Marking requirements.....	15
Table 3	– Conditions for storage before and during discharge testing	20
Table 4	– Resistive loads for tests	21
Table 5	– Time periods for tests.....	21
Table 6	– Test condition tolerances	21
Table A.1	– Items necessary to standardize.....	23
Table C.1	– Physical designation and dimensions of round cells and batteries	27
Table C.2	– Physical designation and nominal overall dimensions of flat cells	28
Table C.3	– Physical designation and dimensions of square cells and batteries	28
Table C.4	– Diameter code for recommended diameter.....	31
Table C.5	– Physical designation and dimensions of round cells and batteries based on Clause C.2	36
Table C.6	– Physical designation and dimensions of non-round batteries based on Clause C.2	37
Table D.1	– Standard discharge voltage by system.....	41