

SRI LANKA STANDARD 916 : PART 1 : 1991

UDC 678.021.17 : 661.666.4

Reaffirmed

2016

SPECIFICATION FOR
RUBBER COMPOUNDING INGREDIENTS

PART 1 - CARBON BLACK - HAF N 330 TYPE

SRI LANKA STANDARDS INSTITUTION

SPECIFICATION FOR RUBBER COMPOUNDING INGREDIENTS
PART 1 : CARBON BLACK - HAF N 330 TYPE

SLS 916:1991

Gr. 4

Copyright Reserved

SRI LANKA STANDARDS INSTITUTION
53, Dharmapala Mawatha,
Colombo 3,
Sri Lanka.

SRI LANKA STANDARD
SPECIFICATION FOR RUBBER COMPOUNDING INGREDIENTS
PART 1 : CARBON BLACK - HAF N 330 TYPE

FOREWORD

This Sri Lanka Standard was authorized for adoption and publication by the Council of the Sri Lanka Standards Institution on 1991-04-02, after the draft, finalized by the Drafting Committee on Rubber Compounding Ingredients had been approved by the Chemicals Divisional Committee.

Clause 4.1 of this specification calls for agreement between the purchaser and the supplier.

This specification covers only the HAF N 330 Type (classification based on ASTM D 1765 : 1989 - Standard classification system for Carbon Blacks used in Rubber products) which is widely used in rubber industry as an ingredient for test mixes.

For the purpose of deciding whether a particular requirement of this specification is complied, with the final value, observed or calculated, expressing the result of a test or an analysis, shall be rounded off in accordance with CS 102. The number of significant places retained in the rounded off value shall be the same as that of the specified value in this specification.

In the preparation of this specification, the assistance obtained from the publications of the International Organization for Standardization, American society for Testing and Materials and British Standards Institution is gratefully acknowledged.

1 SCOPE

This specification prescribes the requirements and methods of sampling and test for carbon black HAF N 330.

2 REFERENCES

CS 102 - Presentation of numerical values
SLS 428 - Random sampling methods
SLS 899 - Methods of Test for rubber compounding ingredients
Part 1 : Carbon black

3 REQUIREMENTS**3.1 Appearance**

The material shall be free from visible impurities.