

SRI LANKA STANDARD 1030 : 1994

UDC 667 . 638.2 : 669.71

**SPECIFICATION FOR
ALUMINIUM WOOD PRIMER**

SRI LANKA STANDARDS INSTITUTION

SPECIFICATION FOR ALUMINIUM WOOD PRIMER

SLS 1030 : 1994

Gr. 6

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
53, Dharmapala Mawatha,
Colombo 3,
Sri Lanka.

SRI LANKA STANDARD
SPECIFICATION FOR ALUMINIUM WOOD PRIMER

FOREWORD

This standard was finalized by the Sectoral Committee on Polymer and Polymer Products and was authorized for adoption and publication as a Sri Lanka Standard by the Council of the Sri Lanka Standards Institution on 1994-12-22.

The aluminium wood primer is suitable for providing a good foundation in respect of sealing properties and prevention of ingress of moisture for the subsequent application of undercoating and finishing.

For the purpose of deciding whether a particular requirement of this specification is complied with, the final value, observed or calculated, expressing the result of a test or an analysis, shall be rounded off in accordance with SLS 102. The number of significant places retained in the rounded off value shall be the same as that of the specified value in this specification.

Guidelines for the determination of compliance of a lot with the requirements of this standard based on statistical sampling and inspection are given in Appendix A.

In the preparation of this standard, the valuable assistance derived from the following publications is gratefully acknowledged :

SS 5		Methods of test for paints, varnishes and related materials
Part B 14	:1987	Determination of pigment content (centrifuge)
Part C2	:1987	Determination of aluminium metal content
SS 38	:1971	Aluminium wood primer
SABS 678	:1973	Primers for wood for interior and exterior use.

1 SCOPE

This specification prescribes the requirements and methods of test for aluminium wood primer to be used on the wood surfaces.