SRI LANKA STANDARD 1278:2006 ISO 13821 : 2002

METHOD OF TESTING OF CORRUGATED FIBREBOARD FOR EDGEWISE CRUSH RESISTANCE (WAXED EDGE METHOD)

SRI LANKA STANDARDS INSTITUTION

SRI LANKA STANDARD METHOD OF TESTING OF CORRUGATED FIBREBOARD FOR EDGEWISE CRUSH RESISTANCE (WAXED EDGE METHOD)

SLS 1278 : 2006 ISO 13821 : 2002

Gr. C

SRI LANKA STANDARDS INSTITUTION 17, Victoria Place Elvitigala Mawatha Colombo – 08 SRI LANKA

SRI LANKA STANDARD METHOD OF TESTING OF CORRUGATED FIBREBOARD FOR EDGEWISE CRUSH RESISTANCE (WAXED EDGE METHOD)

NATIONAL FOREWORD

This Sri Lanka Standard was approved by the Sectoral Committee on Packaging, Paper and Board was authorized for adoption and publication as a Sri Lanka Standard by the Council of the Sri Lanka Standards Institution on 2006-02-21

This standard is identical with ISO 13821 : 2002 Method of Testing of Corrugated Fibreboard for edgewise crush resistance waxed edge method published by the International Organization for Standardization.

The text of the International Standard has been accepted as suitable for publication without deviation, as a Sri Lanka Standard. However certain terminology and conventions are not identical with those used in Sri Lanka Standard. Attention is therefore drawn to the following:

TERMINOLOGY AND CONVENTIONS:

- d) Wherever the words "International Standard" appear referring to a particular standard. They should be interpreted as Sri Lanka Standard.
- e) The comma has been used throughout as a decimal marker. In Sri Lanka Standards it is the current practice to use the full point at the base as the decimal marker.
- f) Wherever page numbers are quoted, they are ISO/IEC numbers

The test temperature adopted in Sri Lanka $27 \pm 2^{\circ}$ C. Relative humidity 65 ± 5 per cent is recommended.

SLS 1278 : 2006 ISO 13821 : 2002

CROSS REFERENCES

International Standard

ISO 186 Paper and board -Sampling to determine average quality

ISO 187 Paper, board & pulps – Standard atmosphere for conditioning and testing and procedure for monitoring the atmosphere and conditioning of samples

ISO 13820 Paper, board and corrugated fibreboard Description and calibration of Compression – Testing equipment

Corresponding Sri Lanka Standard

SLS 808 Methods of sampling paper and board

SLS 374 Standard atmospheric conditions for conditioning and testing

No corresponding standard

SLS 1278:2006

INTERNATIONAL STANDARD

ISO 13821

First edition 2002-09-01

Corrugated fibreboard — Determination of edgewise crush resistance — Waxed edge method

Carton ondulé — Détermination de la résistance à la compression sur chant — Méthode du bord paraffiné



Reference number ISO 13821:2002(E)