SRI LANKA STANDARD 1298 PART 1: 2022 (IEC 60670-1:2015) UDC 621

SPECIFICATION FOR BOXES AND ENCLOSURES FOR ELECTRICAL ACCESSORIES FOR HOUDEHOLD AND SIMILAR FIXED ELECTRICAL INSTALLATIONS

(First Revision)

SRI LANKA STANDARDS INSTITUTION

Sri Lanka Standard SPECIFICATION FOR BOXES AND ENCLOSURES FOR ELECTRICAL ACCESSORIES FOR HOUDEHOLD AND SIMILAR FIXED ELECTRICAL INSTALLATIONS (First Revision)

SLS 1298 PART 1: 2022 (IEC 60670-1:2015)

Gr. V

Copyright Reserved
SRI LANKA STANDARDS INSTITUTION
No. 17, Victoria Place,
Elvitigala Mawatha,
Colombo 08.
SRI LANKA

Sri Lanka Standard SPECIFICATION FOR BOXES AND ENCLOSURES FOR ELECTRICAL ACCESSORIES FOR HOUSEHOLD AND SIMILAR FIXED ELECTRICAL INSTALLATIONS (First Revision)

NATIONAL FOREWORD

This standard was approved by the Sectoral Committee on Electrical Appliances and Accessories and was authorized for adoption and publication as a Sri Lanka Standard by the Council of Sri Lanka Standards Institution on 2022-02-21.

This is the First revision of the **SLS 1298 Part 1: 2022** and identical with IEC **60670: 2015-09, Edition 2.0**, Boxes and enclosures for electrical accessories for household and similar fixed electrical installations published by the International Electrotechnical Commission (IEC).

For the purpose of deciding whether a particular requirement of this standard is complied with the final value, observed or calculated, expressing the results of a test or an analysis shall be rounded off in accordance with **SLS 102**. The number of significant places to be retained in the rounded off value shall be the same as that of the specified value in the standard.

Terminology and conventions

The text of the International Standard has been accepted as suitable for publication with additional information given in the National Appendix. However, certain terminology and conventions are not identical with those used in Sri Lanka Standards; attention is therefore drawn to the following:

- a) Wherever the words "International Standard" appear referring to this standard they should be interpreted as "Sri Lanka Standard".
- b) Wherever the page numbers are quoted they are the page numbers of IEC standard.
- c) The comma has been used as a decimal marker. In Sri Lanka Standards it is the current practices to use a full point on the base line as a decimal marker.
- d) Whenever standard value of rated frequency appears it shall be taken as 50 Hz.

SLS 1298 PART 1: 2022 (IEC 60670-1:2015)

CROSS REFERENCES

International Standard

Corresponding Sri Lanka Standard

IEC 60529 Degrees of protection provided by enclosures (IP Code)

SLS 963 Degrees of protection provided by enclosures (IP Code)

NOTE: Corresponding Sri Lanka Standards for other international standards listed under references in IEC 60670-1 are not available.

NATIONAL APPENDIX

a) Clause 8 MARKING

Add the following immediately after Item j)

- k) Year of manufacture
- 1) Earth symbol on metal enclosures



IEC 60670-1

Edition 2.0 2015-03

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Boxes and enclosures for electrical accessories for household and similar fixed electrical installations –

Part 1: General requirements

Boîtes et enveloppes pour appareillage électrique pour installations électriques fixes pour usages domestiques et analogues –

Partie 1: Exigences générales



CONTENTS

| FO | REWC | RD | | 5 | | |
|---------|----------------------|-----------------------------------|--|----|--|--|
| 1 | Scop | e | | 7 | | |
| 2 | Normative references | | | | | |
| 3 | Term | Terms and definitions | | | | |
| 4 | Gene | General requirements | | | | |
| 5 | | General notes on tests | | | | |
| 6 | Ratings | | | | | |
| 7 | Classification | | | | | |
| 8 | Marking | | | | | |
| 9 | Dimensions | | | | | |
| ا 10 | | | | | | |
| | | Protection against electric shock | | | | |
| 11 | | Provision for earthing | | | | |
| | 11.1 | | and enclosures with exposed conductive parts | 15 | | |
| | 11.2 | | and enclosures of insulating material classified according to 7.2.2.2 2.2.3 | 16 | | |
| | 11.3 | | or enclosures with removable sides according to 7.1.2 | | | |
| | 11.4 | | ng terminal threads | | | |
| 12 | Cons | tructio | n | 18 | | |
| | 12.1 | Gener | al | 18 | | |
| | 12.2 | Lids, d | covers or cover-plates or parts of them | 18 | | |
| | 12.2 | .1 G | Seneral | 18 | | |
| | 12.2 | | crew-type fixing | | | |
| | 12.2 | | lon-screw-type fixing operable without the use of a tool or a key | | | |
| | 12.2 | | on screw-type fixing operable with the use of a tool or a key | | | |
| | 12.3 | | holes | | | |
| | 12.4 | | ing of enclosures | | | |
| | 12.5 | | and enclosures with inlets for flexible cables | | | |
| | 12.6 | | and enclosures with inlets for applications other than flexible cables | | | |
| | 12.7 12.8 | | and enclosures with a cable anchorage(s)s and enclosures with cable retention means | | | |
| | 12.0 | | -outs intended to be removed by mechanical impact | | | |
| | 12.9 | | General | | | |
| | 12.9 | | nock-out retention | | | |
| | 12.9 | | nock-out removal | | | |
| | 12.9 | 4 F | lat surfaces surrounding knock-outs | 29 | | |
| | 12.10 | Screw | fixings | 29 | | |
| | 12.11 | Fixing | of boxes and enclosures classified according to 7.2.1 | 30 | | |
| | 12.12 | | of flush type and semi-flush type boxes and enclosures classified | | | |
| | 40.45 | | ding to 7.2.2.1 | | | |
| | | | and enclosures classified according to 7.2.2.2 and 7.2.2.3 | | | |
| | 12.1 | | Seneral | | | |
| | 12.1 | | oxes intended for mounting to a wood structural member of a wall | | | |
| | 12.1 12.1 | | oxes intended for mounting to a wooden structural member of a ceiling oxes intended for mounting to a steel-stud structural member of a wall | | | |
| | 14. l | J.4 D | oxes interiord for injoining to a steel-stud structural member of a wall | აე | | |

| 12.13.5 Internal volume of boxes and enclosures classified according to 7.2.2.2 and 7.2.2.3 | 36 |
|--|----|
| 12.13.6 Boxes intended for mounting in a finished structure | |
| 12.14 Cable gland entry | |
| 12.15 Boxes and enclosures with inlets (outlets) or spouts (hubs) for conduits | |
| 12.16 Internal volume of boxes and enclosures | |
| 13 Resistance to ageing, protection against ingress of solid objects and against harmful ingress of water | |
| 13.1 Resistance to ageing | 39 |
| 13.2 Protection against the ingress of solid objects | 41 |
| 13.3 Protection against harmful ingress of water | 42 |
| 14 Insulation resistance and electric strength | 47 |
| 15 Mechanical strength | 49 |
| 15.1 General | 49 |
| 15.2 Impact test at low temperature | 49 |
| 15.3 Compression test | 50 |
| 15.4 Impact test for boxes and enclosures | 51 |
| 15.5 Compression test for enclosures made of natural or synthetic rubber or a mixture of both | 56 |
| 16 Resistance to heat | 58 |
| 16.1 Parts of insulating material necessary to retain current-carrying parts | 58 |
| 16.2 Parts of insulating material not necessary to retain current-carrying parts | 59 |
| 16.3 Boxes and enclosures of insulating materials classified according to 7.2.2.2 | |
| or 7.2.2.3 | |
| 16.3.1 Mechanical strength | 58 |
| 16.3.2 Parts of insulating material necessary to retain parts of the earthing circuit | 60 |
| 17 Creepage distances, clearances and distances through sealing compound | |
| 18 Resistance of insulating material to abnormal heat and fire | |
| 19 Resistance to tracking | |
| 20 Resistance to corrosion | |
| 21 Electromagnetic compatibility (EMC) | |
| | |
| Annex A (informative) Examples of enclosures and parts thereof | |
| Bibliography | 65 |
| Figure 1 – Examples of membranes and grommets | 10 |
| Figure 2 – Demonstration of the non-penetration of the internal volume | 15 |
| Figure 3 – Earthing strap | 16 |
| Figure 4 – Test strap | 17 |
| Figure 5 – Arrangement for test on covers or cover-plates (see 12.2.3.2 and 12.2.3.3) | 20 |
| Figure 6 – Gauge for the verification of the outline of lids, covers or cover-plates | |
| Figure 7 – Examples of application of the gauge of Figure 6 on covers fixed without screws on a mounting surface or supporting surface | |
| Figure 8 – Compliance criteria of application of the gauge of Figure 6 | |
| | |
| Figure 9 – Gauge for verification of grooves, holes and reverse tapers | |
| Figure 10 – Sketch showing the direction of application of the gauge of Figure 9 | |
| Figure 11 – Apparatus for testing the cable anchorage | 27 |

| Figure 12 – Example of mounting block for boxes to be embedded in masonry (flush type and semi-flush type) | 32 |
|--|----|
| Figure 13 – Example of the fixing of the auxiliary device mounted on a specimen | 32 |
| Figure 14 – Example of test apparatus for the test | 33 |
| Figure 15 – Verification of fixing means for boxes and enclosures classified according to 7.2.2.1 | 34 |
| Figure 16 – Test of the force and measurement of the displacement | 36 |
| Figure 17 – Volume measurement | 39 |
| Figure 18 – Reference surfaces for boxes and enclosures | 43 |
| Figure 19 – Test wall | 45 |
| Figure 20 – Example of the protected volume | 47 |
| Figure 21 – Apparatus for impact test at low temperature | 50 |
| Figure 22 – Mounting block for flush-type boxes and enclosures in order to apply blows on the rear surface | 52 |
| Figure 23 – Sequence of blows for parts A, B, C, D, E, F and G | 55 |
| Figure 24 – Test devices for load compression test for enclosures made of natural or synthetic rubber or a mixture of both | 58 |
| Figure 25 – Rigid crossbar | 60 |
| Figure 26 – Diagrammatic representation of the glow-wire test | 62 |
| Figure A.1 – Examples of enclosures and parts thereof | 64 |
| Table 1 – Classification of boxes and enclosures (1 of 2) | 12 |
| Table 2 – Forces to be applied to lids, covers, cover-plates or actuating members whose fixing is not dependent on screws | 19 |
| Table 3 – Forces and torques to be applied to cable anchorages | 26 |
| Table 4 – Tightening torques for the verification of the mechanical strength of screws | 30 |
| Table 5 – Torque test values for cable glands | 38 |
| Table 6 – Test voltage for electric strength test | 48 |
| Table 7 – Determination of parts <i>A, B, C, D E, F</i> and <i>G</i> | 52 |
| Table 8 – Height of fall for impact test | 53 |